

# DesignLights Consortium



Classification	Standard
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)
Reported Input Wattage	16 W
Reported Light Output	1950 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	PLD6LILX58CD
DLC Family Code	<a href="#">SSSEEU</a>
Listing Status	Listed
Date Qualified	2021-01-29

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLD6LILX58CD
Manufacturer	SATCO Products Inc
Brand	Satco
Model Number	S11971
Parent	No
Classification	Standard
DLC Family Code	SSSEEU
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	U-Bend Replacement Lamps
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog,Phase Cut,Other Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	160 °
Reported Light Output	1950 lm
Reported Efficacy (AC)	122 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	1
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	1950 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	16 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	16 W

## VERSION HISTORY VIEW DETAILS

2022-04-13	Listed	5.1	Standard
2021-01-29	Listed	5.1	Standard