

# DesignLights Consortium



Classification	Standard
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)
Reported Input Wattage	15.5 W
Reported Light Output	1900 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-R4NQ0V
DLC Family Code	<a href="#">YYFNR</a>
Listing Status	Listed
Date Qualified	2023-02-13

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-R4NQ0V
Manufacturer	SATCO Products Inc
Brand	Satco
Model Number	S18410
Parent	Yes
Classification	Standard
DLC Family Code	YYFNR
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	U-Bend Replacement Lamps
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	Phase Cut,Other Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	160 °
Reported Light Output	1900 lm
Reported Efficacy (AC)	123 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	0
Reported IES Rf	85
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Minimum Light Output	1900 lm
Reported Maximum Light Output	1975 lm
Reported Minimum CCT	3500.0 K
Reported Maximum CCT	5000.0 K
Reported Default Light Output	1900 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	15.5 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	15.5
Reported Default Input Wattage	15.5 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	1881 lm
Tested Efficacy (AC)	125.5 lm/W
Tested CCT	3430 K

Tested CRI (Ra)	85
Tested R9	13
Tested IES Rf	86
Tested IES Rg	97
Tested IES Rcs,h1	-11 %
Tested Duv	-0.001
Tested Beam Angle	162 °

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	15 W
Tested Total Harmonic Distortion	13.8 %
Tested Power Factor	0.956

## PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	<a href="#">Download File</a>
-----------	-------------------------------

## VERSION HISTORY VIEW DETAILS

2023-02-13	Listed	5.1	Standard
------------	--------	-----	----------