DesignLights Consortium





Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	40 W
Reported Light Output	5500 lm
Reported CCT	4000 K
Reported CRI (Ra)	82
Product ID	PL10N0GDSU9Z
DLC Family Code	<u>EMWAFV</u>
Listing Status	Listed
Date Qualified	2021-08-24

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PL10N0GDSU9Z
Manufacturer	SATCO Products Inc
Brand	SATCO PRODUCTS
Model Number	40T8/LED/96-840/BP/FA8(S29918)
Parent	No
Classification	Standard
DLC Family Code	EMWAFV
Length	8.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T8 Eight-Foot
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range Continuous Dimming above 10% Integral Control Capability No Control Capability Sensor Type No Sensor SSL V5 Wired Communication Protocol Other Wired Communication Protocol SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output No White-Tunable No Warm-Dimming No Field Adjustable Light Distribution No		
Sensor Type No Sensor SSL V5 Wired Communication Protocol Other Wired Communication Protocol SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output No White-Tunable No Warm-Dimming No	Dimming Capability and Range	Continuous Dimming above 10%
SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol Field Adjustable Light Output No White-Tunable No Warm-Dimming No	Integral Control Capability	No Control Capability
SSL V5 Wireless Communication Protocol Field Adjustable Light Output No White-Tunable No Warm-Dimming No	Sensor Type	No Sensor
Field Adjustable Light Output No White-Tunable No Warm-Dimming No	SSL V5 Wired Communication Protocol	Other Wired Communication Protocol
White-Tunable No Warm-Dimming No	SSL V5 Wireless Communication Protocol	No Wireless Protocol
Warm-Dimming No	Field Adjustable Light Output	No
	White-Tunable	No
Field Adjustable Light Distribution No	Warm-Dimming	No
	Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	210 °
Reported Light Output	5500 lm
Reported Efficacy (AC)	137 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	82
Reported R9	0
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	5500 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	40 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2021-08-24	Listed	5.1	Standard
------------	--------	-----	----------