DesignLights Consortium





Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	25 W
Reported Light Output	3500 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	PLYF62HN8A9I
DLC Family Code	VVVZCA
Listing Status	Listed
Date Qualified	2020-02-18

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLYF62HN8A9I
Manufacturer	SATCO Products Inc
Brand	SATCO PRODUCTS
Model Number	S39719
Parent	No
Classification	Standard
DLC Family Code	VVVZCA
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp	
General Application	T5HO Four-Foot	
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps	

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Integral Control Capability Sensor Type No Sensor SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol Field Adjustable Light Output White-Tunable No Control Capability No Sensor No Sensor Phase Cut No Wireless Protocol No Wireless Protocol No		
Sensor Type No Sensor SSL V5 Wired Communication Protocol Phase Cut SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output No White-Tunable No	Dimming Capability and Range	Continuous Dimming to 10% or below
SSL V5 Wired Communication Protocol Phase Cut SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output No White-Tunable No	Integral Control Capability	No Control Capability
SSL V5 Wireless Communication Protocol Field Adjustable Light Output White-Tunable No	Sensor Type	No Sensor
Field Adjustable Light Output No White-Tunable No	SSL V5 Wired Communication Protocol	Phase Cut
White-Tunable No	SSL V5 Wireless Communication Protocol	No Wireless Protocol
	Field Adjustable Light Output	No
Warm-Dimming No	White-Tunable	No
	Warm-Dimming	No
Field Adjustable Light Distribution No	Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	180 °
Reported Light Output	3500 lm
Reported Efficacy (AC)	140 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	0
Reported IES Rf	85
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Default Light Output	3500 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	25 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	25 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2020-03-30	Listed	5	Standard
2020-02-18	Listed	4.4	Standard