

# DesignLights Consortium



Model Number	VOLUME6A/S032UNHD8SC7/14U/WH/[Blank,Options]
Classification	Standard
Primary Use	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	32 W
Reported Light Output	4166 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-ET940J
DLC Family Code	<a href="#">CCCHXB</a>
Listing Status	Listed
Date Qualified	2022-12-07

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-ET940J
Manufacturer	LEDVANCE, LLC (formerly OSRAM SYLVANIA, INC)
Brand	LEDVANCE
Model Number	VOLUME6A/S032UNHD8SC7/14U/WH/[Blank,Options]
Parent	Yes
Classification	Standard
DLC Family Code	CCCHXB
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4166 lm
Reported Efficacy (AC)	130.2 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	12
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Minimum Light Output	2720 lm
Reported Maximum Light Output	4166 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4166 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	32 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	20 W
Reported Maximum Input Wattage	32
Reported Default Input Wattage	32 W
Voltage Range	120-347 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	4027 lm

Tested Efficacy (AC)	131.07 lm/W
Tested CCT	3367 K
Tested CRI (Ra)	83
Tested R9	12
Tested IES Rf	85
Tested IES Rg	97
Tested IES Rcs,h1	-11 %
Tested Duv	0.00075

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	30.7 W
Tested Total Harmonic Distortion	4.9 %
Tested Power Factor	0.908

## VERSION HISTORY VIEW DETAILS

2022-12-07	Listed	5.1	Standard
------------	--------	-----	----------