

# 70 Watt Lamps

UNI-FORM PULSE START METAL HALIDE LIGHTING SYSTEMS



## Open Rated LAMPS ANSI Type-O ANSI M98/O featuring UV Shield®

Lamp Description	Product No.	Initial Lumens	LLD	LPW	Rated Life (hrs)	CCT	CRI	Finish	Oper. Pos.	Fig.	Case Qty	Additional Notes
MPL 70W/U/ED28/PS/740	66524	5300	0.80	76	40000	4000K	68	Clear	U	M2	12	
MPL 70W/C/U/ED28/PS/737	35472	5000	0.80	71	40000	3700K	70	Coated	U	M2	12	
MP 70W/U/UVS/PS/EM/950	95071	4800	0.90	69	20000	5000K	90+	Clear	U	B	12	Saves 10 Watts*
MP 70W/C/U/UVS/PS/EM/950	95072	4500	0.90	64	20000	5000K	90+	Coated	U	B	12	Saves 10 Watts*
MP 70W/U/UVS/PS	40389	5300	0.65	76	15000	4000K	65	Clear	U	B	12	
MP 70W/C/U/UVS/PS	67115	5000	0.65	71	15000	3700K	70	Coated	U	B	12	
MP 70W/U/UVS/PS/3K	45424	5300	0.65	76	15000	3200K	65	Clear	U	B	12	
MP 70W/C/U/UVS/PS/3K	14611	5000	0.65	71	15000	3200K	70	Coated	U	B	12	
MP 70W/C/U/ED28/UVS/PS/3K	22466	5000	0.65	71	15000	3200K	70	Coated	U	D	12	

### Benefits

- Compact ED17, T6 and cool-operating ED28 bulbs
- High lumen per watt package
- Superior cold weather starting
- Color temperature and CRI choices
- 50% longer life than CFL's
- UV Shield® lamps available for plastic lens and product protection

## Open Rated LAMPS ANSI Type-O ANSI C139/O

Lamp Description	Product No.	Initial Lumens	LLD	LPW	Rated Life (hrs)	CCT	CRI	Finish	Oper. Pos.	Fig.	Case Qty	Additional Notes
MPC 70W/U/PAR30L/UVS/PS/830/SP10	38827	5000	0.65	71	12000	3000K	83	Clear	U	W	6	MBCP=66000, SP10
MPC 70W/U/PAR30L/UVS/PS/830/FL40	38828	5000	0.65	71	12000	3000K	83	Clear	U	W	6	MBCP=10000, FL40

## Enclosed Rated LAMPS ANSI Type-E ANSI M98/E

Lamp Description	Product No.	Initial Lumens	LLD	LPW	Rated Life (hrs)	CCT	CRI	Finish	Oper. Pos.	Fig.	Case Qty	Additional Notes
MHL 70W/U/ED17/PS/740	15632	5600	0.80	80	40000	4000K	68	Clear	U	I2	12	
MHL 70W/C/U/ED17/PS/737	32618	5300	0.80	76	40000	3700K	70	Coated	U	I2	12	
MHL 70W/U/ED28/PS/740	86501	5600	0.80	80	40000	4000K	68	Clear	U	J2	12	
MHL 70W/C/U/ED28/PS/737	36519	5300	0.80	76	40000	3700K	70	Coated	U	J2	12	
MH 70W/U/PS	78138	5600	0.65	80	15000	4000K	65	Clear	U	A	12	
MH 70W/C/U/PS	12180	5300	0.65	76	15000	3700K	70	Coated	U	A	12	
MH 70W/U/ED28/PS	16017	5600	0.65	80	15000	4000K	65	Clear	U	C	12	

## Enclosed Rated LAMPS ANSI Type-E ANSI C139/E

Lamp Description	Product No.	Initial Lumens	LLD	LPW	Rated Life (hrs)	CCT	CRI	Finish	Oper. Pos.	Fig.	Case Qty	Additional Notes
MHC 70W/U/T4/UVS/PS/930	38808	7800	0.86	111	15000	3000K	91	Clear	U	V	12	
MHC 70W/U/T6/UVS/PS/930	38811	7800	0.86	111	15000	3000K	90	Clear	U	T	12	

NOTE: \* = Benefit is when operating on magnetic ballasts.

### Key

- Natural White®
- Super Pulse Start Ceramic (SPC)
- Super Pulse Start Long Life (SPL)



Dia. = 2.1" (54mm)  
MOL = 5.4" (138mm)  
LCL = 3.4" (86mm)  
Base = Medium (E26)



Dia. = 2.1" (54mm)  
MOL = 5.4" (138mm)  
LCL = 3.4" (86mm)  
Base = Medium (E26)  
Narrow Neck



Dia. = 3.5" (90mm)  
MOL = 8.3" (211mm)  
LCL = 5.0" (127mm)  
Base = Mogul (E39)



Dia. = 3.5" (90mm)  
MOL = 8.3" (211mm)  
LCL = 5.0" (127mm)  
Base = Mogul (EX39)



Dia. = 0.8" (20mm)  
MOL = 3.9" (99mm)  
LCL = 2.2" (56mm)  
Base = G12



Dia. = 0.6" (15mm)  
MOL = 3.3" (85mm)  
LCL = 2.0" (51mm)  
Base = G8.5



Dia. = 3.8" (95mm)  
MOL = 4.5" (114mm)  
Base = Medium (E26)



Dia. = 2.1" (54mm)  
MOL = 5.4" (138mm)  
LCL = 3.4" (86mm)  
Base = Medium (E26)



Dia. = 3.5" (90mm)  
MOL = 8.3" (211mm)  
LCL = 5.0" (127mm)  
Base = Mogul (EX39)



Dia. = 3.5" (90mm)  
MOL = 8.3" (211mm)  
LCL = 5.0" (127mm)  
Base = Mogul (EX39)

