# DesignLights Consortium





Model Number	MRK2220-35K-PLUS[-RP,Blank]
Classification	Standard
Primary Use	Linear Retrofit Kits for 2x2 Luminaires
Reported Input Wattage	21.8 W
Reported Light Output	2851 lm
Reported CCT	3500 K
Reported CRI (Ra)	82.7
Product ID	PT5PM8M5
DLC Family Code	RRRWCH
Listing Status	Listed
Date Qualified	2021-03-02

## **PRODUCT INFORMATION VIEW DETAILS**

Solid State Lighting
5.1
PT5PM8M5
ZLEDLighting
MAGNILUMEN PLUS
MRK2220-35K-PLUS[-RP,Blank]
No
Standard
RRRWCH
AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Troffer
Primary Use Designation	Linear Retrofit Kits for 2x2 Luminaires

#### CONTROL FEATURES VIEW DETAILS

Integral Controls No		No
----------------------	--	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	No Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	2851 lm
Reported Efficacy (AC)	130.6 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82.7
Reported R9	6
Reported IES Rf	85
Reported IES Rg	95
Reported IES Rcs,h1	-11
Reported Minimum Light Output	1044.8 lm
Reported Maximum Light Output	2892.9 lm
Reported Default Light Output	2612 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	21.8 W
Reported Total Harmonic Distortion	15.6 %
Reported Power Factor	0.899
Reported Minimum Input Wattage	8 W
Reported Default Input Wattage	20 W
Voltage Range	100-277 V

#### LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose	
--	-----------------	--

#### **VERSION HISTORY VIEW DETAILS**

2021-03-02	Listed	5.1	Standard
------------	--------	-----	----------