# **DesignLights Consortium**





| Model Number           | MRK2220-40K-PLUS[-RP,Blank]             |
|------------------------|---|
| Classification         | Standard                                |
| Primary Use            | Linear Retrofit Kits for 2x2 Luminaires |
| Reported Input Wattage | 21.8 W                                  |
| Reported Light Output  | 2851 lm                                 |
| Reported CCT           | 4000 K                                  |
| Reported CRI (Ra)      | 82.7                                    |
| Product ID             | PA9KXM6M                                |
| DLC Family Code        | RRRWCH                                  |
| Listing Status         | Listed                                  |
| Date Qualified         | 2021-03-02                              |

#### **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting        |
|--------------------------------|-----------------------------|
| Technical Requirements Version | 5.1                         |
| Product ID                     | PA9KXM6M                    |
| Manufacturer                   | ZLEDLighting                |
| Brand                          | MAGNILUMEN PLUS             |
| Model Number                   | MRK2220-40K-PLUS[-RP,Blank] |
| Parent                         | No                          |
| Classification                 | Standard                    |
| DLC Family Code                | RRRWCH                      |
| Input Power Type               | AC                          |

# PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Retrofit Kit                     |
|-------------------------|---|
| General Application     | Troffer                                 |
| Primary Use Designation | Linear Retrofit Kits for 2x2 Luminaires |

#### **CONTROL FEATURES VIEW DETAILS**

| Integral Controls | No |
|-------------------|----|
|-------------------|----|

| Dimming Capability and Range           | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability            | No Control Capability              |
| Sensor Type                            | No Sensor                          |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol               |
| Field Adjustable Light Output          | Yes                                |
| White-Tunable                          | No                                 |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 2851 lm    |
|-------------------------------|------------|
| Reported Efficacy (AC)        | 130.6 lm/W |
| Reported CCT                  | 4000 K     |
| Reported CRI (Ra)             | 82.7       |
| Reported R9                   | 6          |
| Reported IES Rf               | 85         |
| Reported IES Rg               | 95         |
| Reported IES Rcs,h1           | -11        |
| Reported Minimum Light Output | 1044.8 lm  |
| Reported Maximum Light Output | 2892.9 lm  |
| Reported Default Light Output | 2612 lm    |

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 21.8 W    |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15.6 %    |
| Reported Power Factor              | 0.899     |
| Reported Minimum Input Wattage     | 8 W       |
| Reported Default Input Wattage     | 20 W      |
| Voltage Range                      | 100-277 V |

## **LISTING INFORMATION VIEW DETAILS**

| Testing in a Manufacturer-Selected Housing (Luminaire Specific) | General Purpose |
|---|-----------------|
|---|-----------------|

#### **VERSION HISTORY VIEW DETAILS**

| 2021-03-02 Listed 5.1 Standard |
|--------------------------------|
|--------------------------------|