# **DesignLights Consortium**





Model Number	MRK2330-35K-PLUS[-RP,Blank]
Classification	Standard
Primary Use	Retrofit Kits for Direct Linear Ambient Luminaires
Reported Input Wattage	31.3 W
Reported Light Output	4559.5 lm
Reported CCT	3500 K
Reported CRI (Ra)	83.2
Product ID	PR29MJR8
DLC Family Code	BBBFRI
Listing Status	Listed
Date Qualified	2021-03-03

### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PR29MJR8
Manufacturer	ZLEDLighting
Brand	MAGNILUMEN PLUS
Model Number	MRK2330-35K-PLUS[-RP,Blank]
Parent	No
Classification	Standard
DLC Family Code	BBBFRI
Length	3.0 ft
Input Power Type	AC

## **PRODUCT CATEGORIZATION VIEW DETAILS**

Category	Indoor Retrofit Kit	
General Application	Linear Ambient	
Primary Use Designation	Retrofit Kits for Direct Linear Ambient Luminaires	

## **CONTROL FEATURES VIEW DETAILS**

Integral Controls	No		
Dimming Capability and Range	Continuous Dimming to 10% or below		
Sensor Type	No Sensor		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	Yes		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4559.5 lm
Reported Efficacy (AC)	145.3 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83.2
Reported R9	9
Reported IES Rf	85
Reported IES Rg	96
Reported IES Rcs,h1	-11
Reported Minimum Light Output	1453 lm
Reported Maximum Light Output	4748.4 lm
Reported Default Light Output	4559.5 lm

#### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	31.3 W
Reported Total Harmonic Distortion	11.5 %
Reported Power Factor	0.923
Reported Minimum Input Wattage	10 W
Reported Default Input Wattage	30 W
Voltage Range	100-277 V

## **LISTING INFORMATION VIEW DETAILS**

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
---	-----------------

## **VERSION HISTORY VIEW DETAILS**

2021-03-03	Listed	5.1	Standard