

DesignLights Consortium



Model Number	MRK2330-50K-PLUS[-RP,Blank]
Classification	Standard
Primary Use	Retrofit Kits for Direct Linear Ambient Luminaires
Reported Input Wattage	31.5 W
Reported Light Output	4748.4 lm
Reported CCT	5000 K
Reported CRI (Ra)	83.4
Product ID	PPI9AIZJ
DLC Family Code	BBBFRI
Listing Status	Listed
Date Qualified	2021-03-03

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PPI9AIZJ
Manufacturer	ZLEDLighting
Brand	MAGNILUMEN PLUS
Model Number	MRK2330-50K-PLUS[-RP,Blank]
Parent	Yes
Classification	Standard
DLC Family Code	BBBFRI
Length	3.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Linear Ambient
Primary Use Designation	Retrofit Kits for Direct Linear Ambient Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4748.4 lm
Reported Efficacy (AC)	150.6 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	83.4
Reported R9	9
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Minimum Light Output	1453 lm
Reported Maximum Light Output	4748.4 lm
Reported Default Light Output	4748.4 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	31.5 W
Reported Total Harmonic Distortion	11.8 %
Reported Power Factor	0.923
Reported Minimum Input Wattage	9.648074369189908 W
Reported Default Input Wattage	30 W
Voltage Range	100-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	4748.42 lm
Tested Efficacy (AC)	150.6 lm/W
Tested CCT	4950 K
Tested CRI (Ra)	83

Tested R9	9
Tested IES Rf	84
Tested IES Rg	95
Tested IES Rcs,h1	-12 %
Tested Duv	0.0025

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	31.53 W
Tested Total Harmonic Distortion	11.8 %
Tested Power Factor	0.923

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
---	-----------------

VERSION HISTORY VIEW DETAILS

2021-03-03	Listed	5.1	Standard
------------	--------	-----	----------