# DesignLights Consortium





Model Number	MRK2440-40K-PLUS[-RP,Blank]
Classification	Standard
Primary Use	Linear Retrofit Kits for 2x4 Luminaires
Reported Input Wattage	41.5 W
Reported Light Output	5420.9 lm
Reported CCT	4000 K
Reported CRI (Ra)	83.4
Product ID	P2MKG6JZ
DLC Family Code	RRWCH
Listing Status	Listed
Date Qualified	2021-03-02

### **PRODUCT INFORMATION VIEW DETAILS**

Solid State Lighting
5.1
P2MKG6JZ
ZLEDLighting
MAGNILUMEN PLUS
MRK2440-40K-PLUS[-RP,Blank]
No
Standard
RRRWCH
AC

# PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Troffer
Primary Use Designation	Linear Retrofit Kits for 2x4 Luminaires

#### CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### **REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Reported Light Output	5420.9 lm
Reported Efficacy (AC)	130.5 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83.4
Reported R9	10
Reported IES Rf	85
Reported IES Rg	96
Reported IES Rcs,h1	-11
Reported Minimum Light Output	3132 lm
Reported Maximum Light Output	5763 lm
Reported Default Light Output	5220 lm

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	41.5 W
Reported Total Harmonic Distortion	12.6 %
Reported Power Factor	0.948
Reported Minimum Input Wattage	24 W
Reported Default Input Wattage	40 W
Voltage Range	100-277 V

#### LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose	
--	-----------------	--

## VERSION HISTORY VIEW DETAILS

2021-03-02	Listed	5.1	Standard	
------------	--------	-----	----------	--