DesignLights Consortium





Model Number	MRK2450-50K-PLUS[-RP,Blank]
Classification	Standard
Primary Use	Retrofit Kits for Direct Linear Ambient Luminaires
Reported Input Wattage	49.2 W
Reported Light Output	7381.5 lm
Reported CCT	5000 K
Reported CRI (Ra)	82.2
Product ID	PK2X3KUZ
DLC Family Code	BBBFRI
Listing Status	Listed
Date Qualified	2021-03-03

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PK2X3KUZ
Manufacturer	ZLEDLighting
Brand	MAGNILUMEN PLUS
Model Number	MRK2450-50K-PLUS[-RP,Blank]
Parent	No
Classification	Standard
DLC Family Code	BBBFRI
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Linear Ambient
Primary Use Designation	Retrofit Kits for Direct Linear Ambient Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	7381.5 lm
Reported Efficacy (AC)	150 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82.2
Reported R9	5
Reported IES Rf	83
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3632.5 lm
Reported Maximum Light Output	7381.5 lm
Reported Default Light Output	7381.5 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	49.2 W
Reported Total Harmonic Distortion	10.8 %
Reported Power Factor	0.966
Reported Minimum Input Wattage	24.2166666666666 W
Reported Default Input Wattage	50 W
Voltage Range	100-277 V

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
--	-----------------

VERSION HISTORY VIEW DETAILS

2021-03-03 Listed 5.1 Standard
