

ESPECIFICACIONES DE HYPERSPIN BLOWERS

Modelo	CFM @ 50" de profundida d	m ³ /hr @ 1.27 m de profundida d	Profundida d máxima de operación continua (m)	CFM a Profundida d máxima de operación continua	m ³ /hr a Profundida d máxima de operación continua	HP	Fases	Voltaje	Hz	Peso (kg)
HSB-19.5HP-A38	630.2	1070.0	2.6	530.1	900.0	19.5	3	230-460	60	118
HSB-11.5HP-A36	300.4	510.0	4.0	176.7	300.0	11.5	3	230-460	60	72
HSB-6.5HP-A315	206.2	350.0	2.6	144.3	245.0	6.5	3	230-460	60	45
HSB-4.5HP-A295	159.0	270.0	2.3	126.6	215.0	4.5	3	230-460	60	38
HSB-3.4HP-A273			2.3		170.0	3.4	3	230-460	60	29
HSB-2.5HP-A235	106.6	181.0	2.1	64.2	109.0	2.5	3	230-460	60	24
HSB-1.0HP-A195s	57.7	98.0	1.4	54.2	92.0	1.0	1	230	60	16
HSB-0.5HP-A135s	44.2	75.0	1.6	16.5	28.0	0.5	1	115	60	12