

# HONDA CIVIC SI COUPE/SEDAN 17+ DT-S CATBACK EXHAUST SYSTEM INSTALLATION GUIDE



Congratulations on purchasing the **ARK Performance premium exhaust system!** Please read and understand these instructions before beginning work on the installation of your new ARK Performance exhaust system. If you do not fully understand any of the instructions, please give us a call at 909-947-1ARK (1275) or email us at [support@ARKPerformanceusa.com](mailto:support@ARKPerformanceusa.com)



**Before beginning installation, please verify that you have received all the pieces of your exhaust system. All ARK Performance exhaust systems will come with the exhaust system and hardware (gaskets/clamps and nuts and bolts). If you are missing any pieces, please contact ARK Performance.**

We highly recommend that this exhaust system be installed by **someone qualified for this work or by a certified mechanic** with access to the appropriate hand or power tools. It is also recommended that a lift or hoist be used during the installation. By installing this ARK Performance exhaust system, you indicate that you have read this information guide and you agree with the terms and conditions stated.

It is your responsibility to **follow the instructions** provided for this ARK Performance exhaust system and exercise all necessary safety precautions. ARK Performance assumes no responsibility for damages occurring from improper installation, operation, maintenance, or from incompatibility with other manufacturer's products.

# HONDA CIVIC SI COUPE/SEDAN 17+ DT-S CATBACK EXHAUST SYSTEM INSTALLATION GUIDE



## **Important Information:**

### **Exclusion of Certain Liability:**

1. The manufacturer, importer, and dealer of ARK Performance products hold no responsibility for any incidental damage such as personal injury or any other damages due to improper installation or operation of an ARK Performance exhaust system. When installing an ARK Performance exhaust system, make sure the exhaust system does not touch other parts of the vehicle that are sensitive to high temperature.
2. ARK Performance will not warranty any damages caused by improper installation, use, and maintenance of the ARK Performance exhaust system. The warranty is limited to defects that are recognized by our technical department, this excludes items subject to normal wear such as the flange gaskets. This warranty is void in the case of an accident, modification, improper use, or competition use.
3. Do not install any ARK Performance exhaust system on a vehicle model for which it was not intended for.
4. The exhaust system will be very hot during and immediately after operation of the vehicle, please be careful not to burn yourself on the exhaust system or parts which are in direct contact with it. Also please protect other people, especially children, from any injuries due to the hot exhaust system.
5. Technical specifications of ARK Performance exhaust systems and related products are subject to change without notice.
6. Before removing the original exhaust system from your vehicle, please compare the parts that you received with the list of materials provided in the installation instructions. If anything is missing, contact ARK Performance before beginning installation.
7. The instructions for installation should serve as a guideline only, actual installation of exhaust systems may vary.
8. The process of uninstalling the original exhaust system may vary depending on the existing exhaust system so please follow the original exhaust system manufacturer's instructions for removal.
9. If there are any issues with installation (fitment or missing parts), please contact us right away before continuing. If the exhaust system is modified in any way, there is no refund or warranty.

### **Noise and Emission Warning:**

Because of the world-wide distribution of ARK Performance products, neither ARK Performance nor any of its subsidiaries make any representation that the exhaust system complies with the air and/or noise emissions laws, or labeling laws, of any jurisdiction. The purchasers are entirely responsible for informing themselves of the applicable laws where the products are to be used and to comply with those law.

California laws prohibit the use of any aftermarket exhaust part or system that modifies, removes or replaces original equipment catalysts unless the California Air Resources Board has issued an Executive Order regarding such part or system or unless the part or system is exempted by being used only on racing vehicles on closed courses. Neither ARK Performance nor any of their subsidiaries make any representation that any of their parts or systems has received such an Executive Order or that any of their parts or systems conform with the racing vehicles exemption. The purchasers are entirely responsible for informing themselves of applicable California laws and to comply with those laws. CA Residents: This product may expose you to chemicals including nickel (metallic) and chromium (hexavalent compounds) which are known to the State of California to cause cancer. Learn more at: <https://www.p65warnings.ca.gov/>

Various U.S. states and the U.S. federal government have individual laws regulating the use of aftermarket exhaust parts and systems, especially as those parts and systems modify, remove, or replace original equipment catalysts. Please consult the appropriate laws in your area before installing any aftermarket part or system on your vehicle to ensure compliance with all applicable laws. Neither ARK Performance nor any of their subsidiaries or the sellers of the parts or systems make any representation that any of their parts or systems comply with any such laws.

Trademarks The ARK Performance logo is a registered trademark of ARK Performance Inc. USA.

### Copyright

No part of the ARK Performance exhaust system or its documentation may be reproduced or distributed in any form or by any means without the authorization and permission from ARK Performance Inc. USA.

© ARK Performance Inc. USA. All rights reserved.

# HONDA CIVIC SI COUPE/SEDAN 17+ DT-S CATBACK EXHAUST SYSTEM INSTALLATION GUIDE

## **Included Parts:**

- 1x Rear Pipe w/ Helmholtz Resonator Chamber and Dual Tips
- 1x Front Pipe w/ Resonator
- 1x Mid Pipe
- 1x Triangle Gasket
- 2x 3" Accuseal Clamps

## **Tools Needed:**

- Socket Wrench/Wrench:
  - 14 mm
  - 15 mm
- Socket Wrench Extension
- Lubricant (WD-40)
- Hanger Remover
- Exhaust Stand / A Friend

## **Estimated Installation Time:**

- 1 - 2 hours




## **BEFORE YOU INSTALL:**



- **\*IMPORTANT\*** If any items in the package are missing please contact ARK or your authorized dealer before installation.
- Before removing the original exhaust system, be sure to give sufficient time for the exhaust piping and surrounding parts to cool down. They can be extremely hot!
- We highly advise to have an experienced person or certified mechanic install the exhaust system.
- Raise vehicle only on certified jack stands or on a vehicle lift.
- Please properly dispose of any and all liquids and excess parts that may be produced as a result of removing the existing exhaust system.
- While installing the new system, do not fully tighten nuts and bolts. Begin by loosely fastening all nuts and bolts until everything is installed, then tighten them down to the proper torque specs as you align the exhaust system for best fitment.

# HONDA CIVIC SI COUPE/SEDAN 17+ DT-S CATBACK EXHAUST SYSTEM INSTALLATION GUIDE




## Removal of OEM Exhaust:



1. Remove nuts from front triangular flange using a 14mm socket wrench with the socket wrench extension (Fig. 1). Do not pull out the exhaust system yet. The exhaust system should be resting on the bolts.



2. Brace up the exhaust system with an exhaust stand



3. Slowly remove the exhaust hangers from the rubber insulators with a hanger remover starting from the front of the car to the rear (Fig. 2 & Fig 3.)

4. Finally, slowly remove the exhaust from the three front bolts.

## Installation of the ARK Exhaust System:



1. Lubricate the rubber insulator towards the front of the vehicle and the hanger on the front pipe (Fig. 4). Replace the gasket with the included triangle gasket. Bolt the three nuts of the front pipe to the triangle flange (Fig. 5). Insert the front pipe hanger into the rubber insulator.




# HONDA CIVIC SI COUPE/SEDAN 17+ DT-S CATBACK EXHAUST SYSTEM INSTALLATION GUIDE



**Fig. 6**

2. Loosely fit the two clamps on both ends of the mid pipe. Attach the appropriate end of the midpipe onto the end of the front pipe. Use the 15 mm socket to adjust the tightness of the clamp. Have an exhaust stand or friend to help hold up the midpipe. (Fig. 6)




**Fig. 7** RUBBER INSULATOR RUBBER INSULATOR

3. Lubricate the four rubber insulators near the rear of the vehicle. Slip the rear pipe onto the open end of the mid pipe. (See Fig. 7)

4. Starting from the two hangers closest to the front of the vehicle, place them into the lubricated rubber insulators. Place the last two rear hangers into the rear most two rubber insulators. (See Fig.7)

5. Before tightening the clamps, adjust the alignment of the exhaust tips. Once the tips are properly aligned to your satisfaction, slowly tighten the two clamps on the mid pipes using the 15mm socket wrench. (See Fig. 8)



**Fig. 8**

# HONDA CIVIC SI COUPE/SEDAN 17+

## DT-S CATBACK EXHAUST SYSTEM

### INSTALLATION GUIDE



## First Operation of Vehicle with ARK Performance Exhaust:

- Before starting the vehicle, be sure that no part of the exhaust system is touching a heat sensitive area or an area that will cause a rattle and vibration.
- It is normal to have white smoke and a slight burning smell come from the exhaust system upon first start up and operation. These will eventually go away after 50 miles or more of driving.
- Be sure to check that there are no exhaust leaks, this can be done by revving the motor in neutral to 2,000-2,500 rpm and listening to the piping for any leaks.

## Maintenance:

- Please **DO NOT USE any acidic chemicals or abrasive materials** when cleaning your ARK Performance exhaust system.



- We recommend that you **ONLY USE water and/or automotive soap** when cleaning the Burnt or Tecno tip finishes. **Other chemicals or polishing products MAY REMOVE any finishes.**



- It is recommended to check the nuts and bolts periodically to make sure they have not come loose, re-tighten them if necessary.

