

保護チューブ 選定表

型番	耐熱温度						難燃性	耐候性	EMC	構造	色			環境負荷	サイズ			
	~60°C	~105°C	~125°C	~150°C	~200°C	200°C~	UL規格	あり	シールド効果	後入れ可能	黒	透明	その他	ハロゲンフリー	内径1~19φ	内径20φ~	内径50φ~	内径100φ~
TB	●										●	●	●		●	●		
RBT	●												●		●			
AH		●					●				●	●	●		●			
ETC		●											●		●			
DP	●								●		●	●			●	●	●	
HB	●									●	●		●		●	●	●	●
DKT		●								●								
SKD	●								●	●	●				●	●		
MRX	●								●	●	●				●	●	●	●
TRX	●								●	●	●				●	●	●	
FL			●				●	●		●			●	●	●	●	●	
FLC			●				●					●	●	●	●	●	●	
NFL			●				●	●		●			●	●	●			
FLH				●			●						●					
FLR			●				●	●		●	●				●	●		
FLM-FR			●				●	●		●	●		●	●	●	●	●	
YHK			●					●		●	●				●	●	●	
YHKM			●					●		●	●				●	●	●	
FLA					●				●				●		●	●		
FLAWS					●				●	●			●		●	●		
FLSS						●			●				●		●	●		
FLS				●					●						●	●		
FLSM				●					●	●			●		●	●		
FLG						●							●		●	●	●	
FLGHB						●				●			●		●	●	●	
DP-T						●				●			●		●	●		
ATSX	●								●	●	●				●	●	●	●
FKS	●								●	●	●				●	●	●	●
TRSX	●								●	●	●				●	●	●	
WMR						●				●			●		●	●	●	

●：該当