

# AGROWPLOW®

Prosperity through Soil Care.



AgrowpLOW Head Office  
2 Castle Street  
Molong NSW 2866

1300 722 491  
www.agrowpLOW.com.au  
contact@agrowpLOW.com.au



Some machine options are mutually exclusive, and some can only be used under specific circumstances, or with particular configurations. Some options may increase draft requirements. Consult your AgrowpLOW dealer before considering these options.

All effort has been made to ensure the information presented in this document is correct at the time of publication, however, features and specifications may change without notice.

MODEL	PASTURE SEEDER					
<b>Sowing Rows</b>	12	14	16	20	24	28
<b>Tyre Spacing</b>	150 mm or 175 mm (custom spacings on request)					
<b>Working Width</b>	2.10 m	2.40 m	2.80 m	3.50 m	4.20 m	4.90 m
<b>Transport Width</b>	2.80 m	3.10 m	3.50 m	4.20 m	4.90 m	5.60 m
<b>Hopper Capacity</b>	<b>Front</b>	38 L or 60 L (per metre)				
	<b>Rear</b>	-				
<b>Undercarriage Options</b>	Adjustable height drop-chutes					
<b>Tyre Size</b>	235/75 R15					
<b>Frame</b>	100 x 100 x 6 mm RHS					
<b>Toolbars</b>	1					
<b>Toolbar Spacing</b>	-					
<b>Under Frame Clearance</b>	460 mm					
<b>Linkage Type</b>	Trailing					
<b>Drawbar Power</b>	-					
<b>Weight</b> (without options)	0.6 t (approx)					
<b>Machine Options</b>	-					
<b>Trailing Options</b> (requires rear-tow hitch)	Flexi-Roller Rubber tyre roller					

AD083				AD140				AD240				AD730				
10	11	18	17	10	12	16	20	20	24	24	28	18	22	20	24	28
175 mm	159 mm	150 mm	159 mm	150 mm	150 mm	150 mm	150 mm	150 mm	125 mm	150 mm	125 mm	225 mm	225 mm	175 mm	175 mm	175 mm
1.75 m		2.70 m		1.50 m	1.80 m	2.40 m	3.00 m	3.00 m	3.00 m	3.60 m	3.50 m	4.05 m	4.95 m	3.50 m	4.20 m	4.90 m
2.00 m		2.95 m		2.09 m	2.29 m	2.89 m	3.49 m	3.08 m	3.105 m	3.68 m	3.68 m	4.87 m	5.75 m	4.35 m	5.05 m	5.75 m
245 L		407 L		185 L	215 L	300 L	385 L	605 L	605 L	710 L	710 L	880 L	1080 L	775 L	920 L	1080 L
-		-		185 L	215 L	300 L	385 L	605 L	605 L	710 L	710 L	880 L	1080 L	775 L	920 L	1080 L
425 Coil Tyne	401 Double Disc Unit	425 Coil Tyne	401 Double Disc Unit	425 Coil Tyne 401 Double Disc Unit				425 Coil Tyne				552 HD Spring Tyne 251 Spring Tyne 401 Double Disc Unit				
195 R14				235/75 R15				11.5/80 - 15.3 implement tyres 400/60 - 15.5 optional flotation tyres (increases transport width by 237mm)				380/85 R24				
100 x 100 x 6 mm RHS				100 x 100 x 6 mm RHS				100 x 100 x 6 mm RHS				100 x 100 x 9 mm RHS				
3				3				4				4				
450 mm				440 mm				500 / 670 mm				550 mm				
425 Tyne: 620 mm 401 Disc: 620 mm		425 Tyne: 620 mm 401 Disc: 620 mm		425 Tyne: 620 mm 401 Disc: 620 mm				425 Tyne: 620 mm				552 HD Tyne: 750 mm 251 Spring Tyne: 620 mm 401 Disc: 620 mm				
CAT2 three point linkage				Trailing with hydraulic lift, OR CAT2 three point linkage				Trailing with hydraulic lift				Trailing with hydraulic lift				
60-80 hp		80-100 hp		40-60 hp	60-80 hp	70-90 hp	80-100 hp	80-100 hp	80-100 hp	100-130 hp	100-130 hp	120-150 hp	130-180 hp	120-150 hp	130-160 hp	150-200 hp
1.2 t		1.5 t		1.6 t	1.7 t	1.8 t	2.1 t	2.036 t	2.101 t	2.218 t	2.283 t	3.8 t	4.4 t	3.7 t	4.2 t	4.7 t
Bean roller, Harrows, Rear tow hitch				Bean roller, Coulters, Harrows, Small seeds box, Deep small seeds box, Presswheels, Presswheel small seed tubes, Road kit, Rear-tow hitch, RTH hydraulic kit				Bean roller, Coulters, Double-chuting, Road kit, Harrows, Deep small seeds box, Presswheels, Presswheel small seed tubes, Rear-tow hitch, RTH hydraulic kit				Bean roller, Coulters, Double-chuting, Road kit, Harrows, Deep small seeds box, Presswheels, Presswheel small seed tubes, Small seeds flexi-chutes, Rear-tow hitch, RTH hydraulic kit				
Flexi-Roller Rubber tyre roller				Flexi-Roller, Hydraulic lift kit Rubber tyre roller				Flexi-Roller, Hydraulic lift kit Rubber tyre roller				Flexi-Roller, Hydraulic lift kit Rubber tyre roller				