

TRAILING ROLLERS

Available in a range of working widths to suit your seed drill

FLEXI-ROLLER MK2

Uneven soil is no problem for the Flexi-Roller Mk2. The independent roller rings follow the contours of the earth, providing maximum seed-to-soil contact and ensuring the best possible germination.

The Flexi-Roller is aggressive enough to shatter soil clods and break up crusting yet also gentle enough to lightly press the soil following ploughing or planting. Its rotating action eliminates the need for individual presswheels or soil packers.

Flexi-Rollers may be ordered with or without a hydraulic transport kit that aids in relocating the implement along sealed roads or for extended trips.

RUBBER TYRE ROLLER

The rubber tyre roller is a simple and cost effective way to achieve a firm, consistent seedbed finish. The gang of solid rubber tyres press firmly into the ground, with enough weight to distribute gentle compaction evenly across flat paddocks.

Its action is firm enough to provide a firm seedbed following seeding, but gentle enough to not disturb soil microorganisms or dramatically increase tractor draft requirements.



FLEXI-ROLLER MK2

Adaptable soil finisher for use in primary or secondary tillage as well as seeding operations



Uneven soil is no problem for the Flexi-Roller Mk2. The independent roller rings follow the contours of the earth, providing maximum ground contact and ensuring the best possible seed bed finish, regardless of the soil conditions.

The Flexi-Roller is aggressive enough to shatter soil clods and break up crusting, yet also gentle enough to lightly press the soil following ploughing or planting.

Standard trailing units are available in working widths of 1.65 m up to 5.5 m. The Flexi-Roller Mk2 HD (Heavy Duty) is available in working widths from 4.5 m to 7.5 m. Mounted units are available to suit the AP31.

The roller may be ordered with or without a hydraulic transport kit that aids in relocating the Flexi-Roller along sealed roads or for extended trips.



Your authorised Agrowplow dealer:

Agrowplow Head Office 2 Castle Street Molong NSW 2866

www.agrowplow.com.au 1300 722 491 contact@agrowplow.com.au





