

AGROWPLOW

AUSTRALIAN
DESIGNED & MADE



CP62 SPECIFICATIONS Working Width 6.0 m Side or Centre Bust Centre Side **Number of Shanks** 13 19 **Shank Spacing** 500 mm 333.33 mm **Number of Furrows** 7 1000 mm **Furrow spacings Maximum Working Depth** 600 mm **Shank Style** #9 Rigid Assembly **Rigid Shear Pin Breakout** 4,790 kg (10,560 lbs) at blade Frame 150 x 150 x 9 mm RHS No. Toolbars / Spacing 3 / 725 m **Depth Wheels** Dual 11.5/80-15.3 6-stud Bedford Linkage Type CAT3 three point linkage & CAT3 quick hitch **Drawbar Power** 260-390 hp 380-570 hp 6,490 mm (w) x 2,700 mm (d) x 1,730 mm (h) **Transport Dimensions** (with stabiliser: 2,550 mm height) Weight 2,550 kg 2,900 kg **Machine Options** Plough Stabiliser Arm (adds 315 kg) **Furrowers** Shank Options¹ Mulch blades

LEARN MORE



- Price and configure
- **⊘** View full features
- View tyne layouts

AGROWPLOW SALES:

Chris Beatty: 0477 299 592 Mark Gavin: 0429 393 350 sales@agrowplow.com.au

YOUR LOCAL DEALER:







