HIGH PRESSURE CLEANERS



SEMI PROFESSIONAL



3200









APPLICATIONS



Domestic Cleaning



Tradesmen



Commercial Cleaners



Agriculturist





STANDOUT FEATURES



AAA[™] triplex plunger pump delivers performance & reliability.



Industrial Honda[™] GX200 pull start series engine.



13" premium pneumatic tyres.



0°, 15, 25, 40 and snap-on nozzles.



Jetwave Safety System[™] (JSS) thermal and safety valve to prevent overheating in excessive bypass and over pressurisation.



Dual M22 screw hose coupling system.





TECHNICAL DATA 0:00		JLACC GX CAGE	
Product Code		HP220-10PWN	
Pressure / Flow Rate		3200 PSI (220 BAR) / 10.6 L/PM	
Max Inlet Temp		60°C	
Class (ASNZS: 4223)		A (2,332 Bar/Litres)	
Usage Frequency		Semi Professional: 1-3 Hours a Week	
Nozzle Size		03	
Frame Structure		Heavy duty steel black powder coat 4-wheel trolley	
MOTOR FEATURES	Ĵ0		
Engine / Power		Honda [™] GX200 Pull Start (air cooled) 6.5HP / 200cc	
Fuel Type / Capacity / Protection		Unleaded / 4.5L / Low Oil Shutdown	
HYDRAULIC FEATURE	s 🟨		
Pump / Head / Pistons		Plunger Triplex / Brass / Ceramic Coated	
Motor Pump Coupling / Pump RPM		Direct Drive / 3400RPM	
Unloader Valve		Integral	
Safety Valve		Yes	
Detergent Injector		Yes - Downstream low pressure	
DIMENSIONS & WEIGI	HT 🗊		
Machine Dimensions / Weight		750mm(L) x 610mm(W) x 680mm(H) / 50KG	
WARRANTY(S) 父			
Unit / Pump Warranty*		1 Year	
Engine Warranty*		📷 🔜 3 Years	
OPTIONAL ACCESSOR	RIES		
10m Extension Hose + M22 Joiner	JWA018-EX		
Turbo Head with Snap Tail	JWA303		
JW3 Foaming Lance with Tank	JWA221		
15" Hammerhead with Lance	JWA-FSC15-CMPL		

The manufacturer reserves the right to modify design features and technical facts without notice; due to our principals of continuous improvement. *Coverage against defects in material and workmanship (refer to Jetwave's and component partners T&Cs).

V2.2 08/21