





















Ledlenser Directory

POWERUP




POWERUP ON WEB



ENJOY LONGER

CALL AND THE OWNER

CREATE **MEMORIES**



2-3 CONTENT

4-9 NEW PRODUCTS

- 9 HF4R Core NEW
- 9 HF6R Core NEW
- 9 HF8R Core NEW
- HEADLAMPS

14 H5 Core

- 14 H5R Core 15 H7R Core 15 H15R Core
 - 15 H19R Core
 - 16 H19R Signature

20-23 MH-SERIES

20 MH3



- 20 MH421 MH5
- 22 MH722 MH8
- 23 MH11

24-27 NEO-SERIES

- 26 NE01R 27 NE03 27 NE05R
 - 27 NE09R
 - 28-29 CLIPLIGHT
 - 29 CU2R
 - 30-33 KEYRING LAMPS
 - 32 K4R 33 K6R
 - 33 K6R Safety

34-39 KIDSLIGHTS

- 37 KIDLED237 KIDLED4R
- 38 KIDBEAM4 38 KIDCAMP6

CONTENT OUTDOOR & SPORTS HOME & LIFE

40-45 LANTERNS

- 44 ML4
- 44 ML4 WL
- 45 ML6
- 45 ML6 WL
- 45 ML6 WL Connect

46-51 PORTABLE ENERGY

- 48 FLEX5
- 48 FLEX10
- 50 FLEX3
- 50 FLEX7


52-69 FLASHLIGHTS

- 54 P2R Core
- 54 **P3 Core**
- 55 P4 Core
- 55 P4R Core
- 56 **P5 Core**
- 56 P5R Core
- 57 P6 Core
- 57 P6R Core
- 61 P7 Core
- 61 P7R Core
- 62 P17R Core
- 64 P6R Core QC
- 65 P6R Signature
- 65 P7R Signature
- 67 P18R Signature
- 69 MT10
- 69 MT14
- 70 ACCESSORIES72-77 TECHNOLOGIES78-79 ABOUT US80-81 WARRANTY + ISO





THE HF-SERIES






NEW **REVOLUTIONARY** TECHNOLOGIES

HF8RCORE 2000 NEW

REVOLUTIONARY TECHNOLOGIES FOR MAXIMUM FLEXIBILITY:

With the HF8R, Ledlenser introduces its first hands-free headlamp. Why break your flow at work when your headlamp will adjust automatically or transition seamlessly, while providing you with the perfect light pattern. Without a battery box at the back of your head or an additional cable at the headband, you will be more comfortable and move more freely. 03 02





03

01 – **Powerful headlamp** with additional red front light

LEDLEDSER

05

- - completely hands-free.
- Magnetic Charge System
- 04 Water and dustproof (IP68)
- 06 Lamp head tilts steplessly
- focusing thanks to our D
- **08** High-quality **aluminum housing**
- additional features available)

TRULY HANDS-FREE DIMS AND FOCUSES AUTOMATICALLY



-;**ċ**;-1600 lm¹ **□**; 210 m¹ **○** 90 h¹

02 - Automatic dimming and focusing thanks to our Adaptive Light Beam Technology – the system detects reflections and lighting conditions and automatically controls all light sources separately. This allows the HF8R to be used **03** – **Powerful battery** can easily be recharged via **05** – Large scope of delivery for versatile options and use 07 – Perfect light pattern for any range and virtually seamless optional manual operation via Focus Wheel 09 – Remote control via Ledlenser Connect App (upgrade with

HF4R Core: Entry-level model – ideal for walking the dog or camping

旧

NEW



HF6R Core: A step up – suitable for hiking or more ambitious DIY projects



HF8R Core: The power package – when in doubt, rely on our adaptive powerhouse

| \bigcirc | LED Configuration |
|--|--|
| | Linkt Exection - |
| all | Light Functions |
| <u>-ờ-</u> | Luminous Flux ¹ (lm) |
| ⇒ | Beam Distance ¹ (m) |
| \bigcirc | Run Time ¹ (h) |
| Вĸ | Color Temperature (K) |
| (CRI) | Color Rendering Index (CRI) |
| В | ATTERY AND CASE |
| E Composition de la compositio | Battery |
| | Battery Capacity ² (Wh / mAh) |
| Ġ | IP Level |
| • ② | Rechargeable |
| Þ | Charging Time ⁵ (min) |
| Ŷ | Drop Height (m) |
| W | /EIGHT |
| டு | Weight incl. Battery (g / oz) |
| Т | ECHNOLOGIE |
| 11 | Adaptive Light Beam |
| | Digital Advanced Focus System |
| | Magnetic Charge System |
| | Temperature Control System |
| | Cooling Technology |
| - | More Features |
| | |
| | |
| Р | ACKAGING |
| | ltem no. Box / GTIN |
| | Item no. Box / GTIN |

Item no. Box / GTIN

Content Box

| PRODUCT VDEO | PRODUCT VIDEO | PRODUCT VID |
|--|--|--|
| eable | esble | etter |
| HF <mark>4R</mark> CORE | HF6R CORE | HF <mark>8R</mark> CORE |
| 2x High Power LED, 1x Red LED | 2x Xtreme LED, 1x High Power LED, 1x Red LED | 3x Xtreme LED, 1x High Power LED, 1x Red LED |
| Boost / Power / Mid Power / Low Power (+ Red Light) | Boost / Power / Mid Power / Low Power (+ Red Light) | Boost / Power / Mid Power / Low Power (+ Red Light) (+S.O.S., Alpine distress signal via A |
| 500 / 300 / 120 / 20 | 800 / 500 / 250 / 20 | 1600 / 900 / 300 / 20 |
| 130 / 100 / 60 / 15 | 160 / 140 / 80 / 25 | 210 / 200 / 100 / 25 |
| - / 2.5 / 5 / 35 | -/3/6/60 | - / 3.5 / 10 / 90 |
| 5200 - 6200 | 5200 - 6200 | <u>-</u> <u>5200 - 6200</u> |
| 70 | 70 | 70 |
| | | |
| 1x Li-ion Battery Pack 3.7V | 1x Li-ion Battery Pack 3.7V | 1x Li-ion Battery Pack 3.7V |
| 3.7 / 1000 | 7.4 / 2000 | 13.7 / 3700 |
| IP68 | IP68 | |
| Yes | Yes | Yes |
| 180 | 225 | 270 |
| 2 | 2 | 2/0 |
| <i>L</i> | | |
| | | |
| 72 / 2.54 | 126 / 4.44 | 194 / 6.84 |
| | | |
| | | |
| | • | |
| • | <u> </u> | |
| • | • | |
| | <u> </u> | • |
| Fusion Beam, Transportation Lock, Memory Function, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning | Memory Function, Transportation Lock, Backup Mode, Aluminum housing, Battery Indicator, Charge Indicator, Low Battery Warning | Bluetooth®, Transportation Lock, Memory Function, Backup Mode, Aluminum housing Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning |
| Black: LL502790 / 4058205031684 | Black: LL502796 / 4058205031837 | Black: LL502801 / 4058205031943 |
| Blue: LL502791 / 4058205031707 | Blue: LL502966 / 4058205034319 | |
| Red: LL502792 / 4058205031738 | Red: LL502967 / 4058205034340 | |
| - NEU. LEJUZ/72/ 40J0203031/30 | | |
| Connect Adapter, Magnetic Charging Cable (USB-C) | O White: LL502797 / 4058205031851 Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C) | Comfort Pad, Connect Adapter, Magnetic Charging Cable (USB-C), removable Overhead Strap |





HEADLAMPS







- H7R CORE












- **01** Intuitive operation and stepless dimming thanks to the Wheel switch on the lamp head
- 02 Strong dust and water predection (IP67)
- 03 Stepless swivel mechanism for vertical alignment of the light cone
- 04 Advanced Focus System stepless focusing
- **05** Convenient and safe charging of the battery thanks to the Magnetic Charge System
- 06 Integrated battery and charge status indicator
- 07 Ledlenser Connecting System one interface for many accessories

ELEGANT ILLUMINATION





—H-SERIES CORE

| | LEDLENSER | LED.ETTER |
|--------------------------------------|---|--|
| | | |
| | H5 CORE | H5R CORE |
| LED | | |
| ❑ LED Configuration | 1x High Power LED | 1x High Power LED |
| ILII Light Functions | Boost / Power / Low Power | Boost / Power / Low Power |
| Ọ́- Luminous Flux¹(lm) | 350 / 200 / 15 | 500 / 300 / 15 |
| ⊐⇒ Beam Distance¹ (m) | 160 / 120 / 30 | 200 / 150 / 30 |
| Bun Time ¹ (h) | - / 2 / 20 | - / 2 / 50 |
| ^{[]K} Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| R) Color Rendering Index (CRI) | 70 | 70 |
| BATTERY AND CASE | | |
| ⊡ Battery | 2x Mignon (AA) Alkaline 1.5V | 1x Li-ion Battery Pack 3.7V |
| ⊡ Battery Capacity² (Wh / mAh) | - | 6.66 / 1800 |
| ہے۔ IP Level | IP67 | IP67 |
|) Rechargeable | No | Yes |
| - ℃ Charging Time⁵ (min) | - | 210 |
| L Drop Height (m) | 1.5 | 1.5 |
| SIZE AND WEIGHT | | |
|) Head Diameter (mm) | 32 | 32 |
| g Weight incl. Battery (g / oz) | 178 / 6.3 | 167 / 5.9 |
| TECHNOLOGY | | |
| Multi-Core Optics | | |
| Flex Sealing Technology | • | |
| Magnetic Charge System | | |
| Fusion Beam | | |
| Advanced Focus System | • | |
| More Features | Cooling Technology, Dimmable, Transportation Lock, Energy Saving | Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indica- tor, Charge Indicator, Low Battery Warning, Constant Light |
| PACKAGING | | |
| Item no. Box / GTIN | LL502193 / 4058205020848 | LL502121 / 4058205020879 |
| | | |

| PRODUCT VIDEO | PRODUCT VIDEO | PRODUCT VIDEO |
|--|---|--|
| Contraction of the second seco | | Seable Street |
| H7R CORE | H15R CORE | H19R CORE |
| 1x Xtreme FD | 1x Xtreme LED | 2x Xtreme LED |
| | | |
| Boost / Power / Low Power 1000 / 600 / 15 | Boost / Power / Low Power 2500 / 1000 / 20 | Boost / Power / Mid Power / Low Power 3500 / 1600 / 800 / 200 |
| 250 / 200 / 25 | 250 / 170 / 20 | 300 / 230 / 150 / 80 |
| - / 4 / 65 | - / 5 / 80 | -/4/7/20 |
| 6000 – 7500 | | <u>-</u> <u></u> |
| 70 | 70 | 70 |
| | | |
| 1x 21700 Li-ion Battery 3.7V | 1x Li-ion Battery Pack 7.4V | 1x Li-ion Battery Pack 7.4V |
| 17.76 / 4800 | 35.52 / 4800 | 35.52 / 4800 |
| IP67 | | |
| Yes | Yes | Yes |
| 210 | 330 | 330 |
| 1.5 | 1.5 | 1.5 |
| | | |
| 41 | 47 | 68 |
| 259 / 9.1 | 380 / 13.4 | 374 / 13.2 |
| | | |
| | • | • |
| • | • | - |
| • | • | • |
| | | • |
| • | • | |
| Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light | Cooling Technology, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light | Temperature Control, Cooling Technology, Optisense Technology, Dimmable, Trans- portation Lock, Flicker-free, Memory Mod Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light, Red Light |
| | | |
| LL502122 / 4058205020909 | LL502123 / 4058205020930 | LL502124 / 4058205020961 |
| 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable |

| f Batteries, | |
|-------------------|--|
| ic Charging Cable | |

Content Box

1 Set of Batteries

1 Set of Batteries, Magnetic Charging Cable

- H19R SIGNATURE

THE FLAGSHIP OF THE SIGNATURE RANGE -;¢;-4000 lm¹ □;) 330 m¹ ⊙ 20 h¹







01 02

- $\cap 7$

- **01 Fusion Beam** individually adjustable flood and spotlight for a unique light image with perfect illumination
- 02 Multi-Core Optics homogeneous light image thanks to special faceting of the lens
- 03 Ledlenser Connect App and Bluetooth® remote control enable personalization and remote control of the light functions
- 04 Optisense Technology automatic adaptation to the light conditions thanks to the integrated sensor
- 05 Extreme Dust and Water Protection (IP68)
- 06 Additional Red Light to maintain night vision
- 07 Stepless Swivel Mechanism for vertical alignment of the light cone **08 – Ledlenser Connecting System –** one interface for many accessory parts
- 09 Additional Content: 1. Bluetooth® remote control, 2. Battery, 3. USB power adapter, 4. Magnetic charging cable, 5. Extension cable 6. Helmet connecting kit, 7. Helmet clips, 8. GoPro Adapter, 9. Universal holder, 10. Stand holder ► Supplied in a soft case
- 10 Reflective Headband

) LEDLENSER



03





-H-SERIES SIGNATUR



| | PRODUCT VIDEO | H7R SIGNATURE | H19R SIGNATURE |
|---------------|--|--|---|
| L | ED | | |
| \bigcirc | LED Configuration | 1x Xtreme LED | 1x Xtreme LED |
| 411 | Light Functions | Boost / Power / Low Power (+ Strobe, Positon, SOS und Blink) | Boost / Power / Mid Power / Low Power (+ Strobe, Positon, SOS und Blink) |
| <u>-ờ́-</u> | Luminous Flux ¹ (lm) | 1200 / 700 / 15 | 4000 / 1800 / 800 / 200 |
| <u>ل</u> | Beam Distance ¹ (m) | 260 / 220 / 25 | 330 / 250 / 150 / 80 |
| Ŀ | Run Time ¹ (h) | - / 3.5 / 65 | - / 3.5 / 7 / 20 |
| <u>В</u> к | Color Temperature (K) | | 6500 |
| (CRI) | Color Rendering Index (CRI) | 80 | 80 |
| В | ATTERY AND CASE | | |
| iiiii) | Battery | 1x 21700 Li-ion Battery 3.7V | 1x Li-ion Battery Pack 7.4V |
| III •1 | Battery Capacity ² (Wh / mAh) | 17.76 / 4800 | 35.52 / 4800 |
| ¢ | IP Level | | <u>IP68</u> |
| Ŷ | Rechargeable | Yes | Yes |
| Ō | Charging Time⁵ (min) | 210 | 330 |
| Ţ | Drop Height (m) | 1.5 | 1.5 |
| S | IZE AND WEIGHT | | |
| \bigcirc | Head Diameter (mm) | 41 | 68 |
| ß | Weight incl. Battery (g / oz) | 259 / 9.1 | 374 / 13.2 |
| Т | ECHNOLOGY | | |
| \odot | Fusion Beam | | • |
| | Flex Sealing Technology | • | |
| 00 | Magnetic Charge System | • | • |
| | Temperature Control | • | • |
| | Advanced Focus System | • | |
| | More Features | Cooling Technology, Emergency Light, Bluetooth® ⁸ , Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light | Mutli-Core Optics, Red Light, Optisense, Cooling Technology, Emergency Light, Bluetooth®, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Battery Indicator, Charge Indicator, Low Battery Warning, Constant Light |
| Ρ | ACKAGING | | |
| | Item no. Box / GTIN | LL502197 / 4058205021081 | LL502198 / 4058205021111 |
| | Content Soft Case | 1 Set of Batteries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps Adhesive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable | Bluetooth ^{®®} remote control, 1 Set of Batte- ries, Helmet Clips, Adapter for GoPro, Helmet Holder, Hook-and-Loop straps, Ad esive Pads, Magnetic Charging Cable, Tripod Holder, USB Power Adapter, Universal Holder, Extension Cable, Adhesive Pads |

THE ULTIMATE LIGHTING FOR THE HIGHEST DEMANDS

-MH-SERIES




MH3



| LED | | |
|---------------------------------|------------------------------|--|
| △ LED-Configuration | 1x High Power LED | 1x High Power LED, 1x Red LED |
| IIII Light Functions | Power / Low Power | Power / Low Power |
| -՝Ų́- Luminous Flux¹ (lm) | 200 / 20 | 400 / 20 |
| ⊏⊐→ Beam Distance¹ (m) | 130 / 40 | 180 / 40 |
| Run Time ¹ (h) | 4,5 / 35 | 4 / 35 |
| BATTERY AND CASE | | |
| 페 Battery | 1x Mignon (AA) Alkaline 1,5V | 1x 14500 Li-ion Battery 3,7V |
| 🖦 Battery Capacity² (Wh / mAh) | _ | 2,77 / 750 |
| 🖞 Rechargeable | No | Yes |
| ট Charging Time⁵ (min) | _ | 150 |
| ကို IP Level | IP54 | IP54 |
| SIZE AND WEIGHT | | |
| 🔘 Head Diameter (mm) | 31 | 31 |
| 🕱 Weight incl. Battery (g / oz) | 92 / 3,2 | 94 / 3,3 |
| TECHNOLOGY | | |
| 🚻 Smart Light Technology | • | • |
| 🕑 Rapid Focus | • | • |
| 🚯 Dual Power Source | • | • |
| 🚭 Advanced Focus System | • | • |
| 💿 Magnetic Charge System | | • |
| More Features | Low Battery Warning | Low Battery Warning, Battery Indicator, Charge Indicator, Red Light |
| | | |

PACKAGING FARBVARIANTEN Item no. Window Box / GTIN LL501597 Black / 4058205014656 LL502151 Black / 4058205020121 Contents Box 1 Set of Batteries 1 Set of Batteries, Magnetic Charging Cable



1 Set of Batteries, Magnetic Charging Cable

03









01 – Advanced Focus System – stepless focusing 02 - Innovatives Mounting System enables

easy to remove and put on lamp head and battery

03 – Numerous attachment options using metal clips on the lamp head

04 – Red Light Function to maintain the

night vision ability

05 – Variable **swivel mechanism** for aiming the light cone


06 – Dual Power Source – rechargeable or primary battery, this technology allows for both **07** – Convenient and safe charging of the batteries

thanks to Magnetic Charge System **08 – Battery Indicator** and **Charge Indicator**

MH-SERIES

| | PRODUCT VIDED | PRODUCT VIDEO |
|---------------------------------|--|--|
| | MH7 | MH8 |
| LED | | |
| \cap LED-Configuration | 1x Xtreme LED, 1x Red LED | 1x Xtreme LED, 1x Multicolor LED |
| 베 Light Functions | Boost / Power / Mid Power / Low Power (+ Blink) | Boost / Power / Mid Power / Low Power (+ Blink) |
| | 600 / 400 / 170 / 20 | 600 / 400 / 170 / 20 |
| ⊐ ⊐ → Beam Distance¹ (m) | 200 / 180 / 120 / 40 | 200 / 180 / 120 / 40 |
| 🕒 Run Time¹ (h) | - / 7 / 10 / 60 | - / 7 / 10 / 60 |
| BATTERY AND CASE | | |
| ⊡ Battery | 1x Li-ion Akkupack 3,7V | 1x Li-ion Akkupack 3,7V |
| Battery Capacity ² | 5,73 / 1550 | 5,73 / 1550 |
| D Rechargeable | Yes | Yes |
| ら Charging Time⁵ (min) | 270 | 270 |
| က္ IP Level | IP54 | IP54 |
| SIZE AND WEIGHT | | |
| 🕥 Head Diameter (mm) | 31 | 31 |
| Weight incl. Battery (g / oz) | 139 / 4,9 | 139 / 4,9 |
| TECHNOLOGY | | |
| Smart Light Technology | • | • |
| Rapid Focus | • | • |
| Dual Power Source | • | • |
| 🕀 Advanced Focus System | • | • |
| Magnetic Charge System | • | • |
| 🕖 Optisense Technology | | |
| More Features | Cooling Technology, Energy Saving, Constant Light, Low Battery Warning, Charge Indicator, Battery Indicator, Red Light, Transportation Lock | Cooling Technology, Energy Saving, Cons- tant Light, Low Battery Warning, Charge Indicator, Battery Indicator, Red Light, Green Light, Blue Light, Transportation Lock |

| PACKAGING | | |
|----------------------------|---|---|
| Item no. Window Box / GTIN | LL501599 Black / 4058205014700 | LL502156 Black / 4058205019996 |
| Contents Box | 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cable |



Constant Light, Low Battery Warning, Charge Indicator, Battery Indicator, Red Light, Green Light, Blue Light, Transporta-tion Lock, Bluetooth®⁸, Dimmable, Memory Mode, Temperature Control System

LL500996 Black / 4058205013833

1 Set of Batteries, Magnetic Charging Cable, Belt Pouch


LIGHT ENGINEERED B

NEO-SERIES

LIGHTER, SMALLER, FASTER

The new Ledlenser NEO series provides you with the perfect light to bring out the best in you during fast-paced activities in the dark. Your NEO headlamp is your partner on the way to your next goal - no matter whether you run on or off the trails, skate, parkour or practice other fast-paced sports where customized lighting is essential. The headlamps of the NEO series are optimized in every detail for their intended use – from the perfect light image and clever light functions to weight, size and sophisticated details.

























Perfect light pattern for fast-moving activities with combined close and long distance light





Extremely powerful trail running headlamp with outstanding light image; multiple light sources perfectly illuminate near and far in every situation



ULTRALIGHT AND VERSATILE



Additional red light as a



Quick and easy battery signal light and to maintain charging via Magnetic Charge System with status LED



Tilting lamp head for individual adjustment of the light cone

BRIGHT ALLROUNDER FOR SPORTY MISSIONS



Perfect light pattern for



Tilting lamp head for individual adjustment of the light cone



Minimalist, ergonomic design with cable tunnel for perfect fit and wearing; 360° visibility thanks to red flashing rear light; easy operation with three AAA batteries

COMPACT POWER FOR AMBITIOUS ATHLETES





360° visibility thanks to red flashing rear light and reflective headband; quick and easy battery charging via Magnetic Charge System with status LED



Tilting lamp head for individual adjustment of the light cone

THE PERFECT LIGHT FOR TRAIL RUNNERS



Extremely powerful, replaceable battery pack; rechargeable via Magnetic Charge System with status LED



Ergonomic design with removable overhead strap for perfect fit and wearing comfort during outdoor activities: included chest belt as additional attachment option



| | PRODUCT VIDEO |
|---|---|
| | NEO1R |
| | |
| LED Configuration | 1x High Power LED |
| ·∭ Light Functions -Ċ- Luminous Flux¹(lm) | Boost / Power / Low Power 250 / 150 / 20 |
| $\rightarrow \gamma^{-}$ Lummous Flux (iiii) $\Box \rightarrow$ Beam Distance ¹ (m) | 80 / 50 / 15 |
| Run Time ¹ (h) | - / 3 / 15 |
| BATTERY AND CASE | 7 5 7 1 5 |
| BATTERT AND CASE | 1x Li-ion Battery Pack 3.7 V |
| Battery Capacity ² (Wh / mAh) | 2.7 / 730 |
| | Yes |
| Pechargeable Charging Time⁵ (min) | 180 |
| 아 IP Level | IP67 |
| SIZE AND WEIGHT | |
| Head Diameter (mm) | 48 |
| Weight incl. Battery (g / oz) | 39 / 1.4 |
| TECHNOLOGY | |
| Fusion Beam | |
| Magnetic Charge System | • |
| Temperature Control | - |
| More Features | Low Battery Warning, Battery Indicator, Charge Indicator, Red Light, Transportation Lock, Backup Mode |
| PACKAGING | |
| ltem no. Box / GTIN | LL502713 Blue/Black / 4058205029971 |
| ltem no. Box / GTIN | LL502720 Lime/White / 4058205030168 |
| ltem no. Box / GTIN | LL502712 Grey/Black / 4058205029957 |
| Content Box | Magnetic Charging Cable |

| PRODUCT VIDEO | PRODUCT VIDEO | |
|--|--|--|
| NEO3 | NEO5R | NEO9R |
| | | |
| 2x High Power LED | 2x High Power LED | 3x Xtreme LED |
| Boost / Power / Mid Power / Low Power | Boost / Power / Mid Power / Low Power | Boost / Power / Mid Power / Low Power |
| 400 / 200 / 100 / 20 | 600 / 300 / 100 / 20 | 1200 / 600 / 200 / 20 |
| 80 / 60 / 40 / 5 | 100 / 70 / 40 / 5 | 200 / 120 / 60 / 5 |
| -/3/6/20 | - / 4 / 8 / 35 | - / 5 / 12 / 120 |
| | | |
| 3x Micro (AAA) Alkaline 1.5V | 1x Li-ion Battery Pack 3.7 V | 2x 18650 Li-ion Battery Pack. 3.7V |
| - | 6.66 / 1800 | 18.5 / 5000 |
| No | Yes | Yes |
| | 240 | 330 |
| IP54 | IP54 | IP54 |
| | | |
| 41 | 41 | 57 |
| 97 / 3.4 | 106 /3.7 | 199 / 7.0 |
| | | |
| | | • |
| | | |
| • | | |
| Low Battery Warning, Battery Indicator, Rear Light, Transportation Lock, Backup Mode | Low Battery Warning, Battery Indicator, Charge Indicator, Rear Light, Transportation Lock, Backup Mode | Low Battery Warning, Battery Indicator, Charge Indicator, Rear Light, Transportation Lock, Backup Mode |
| | | |
| LL502718 Blue/Black / 4058205030106 | LL502716 Blue/Black / 4058205030052 | LL502715 Blue/Black / 4058205030021 |
| LL502719 Lime/White / 4058205030137 | LL502323 Grey/Black / 4058205024136 | LL502324 Grey/Black / 4058205024167 |
| LL502717 Grey/Black / 4058205030083 | | |
| 1 Set of Batteries, Comfort Pad | 1 Battery Pack, Magnetic Charging Cable, Comfort Pad, Chest Strap | 1 Battery Pack, Magnetic Charging Cable, Comfort Pad, Overhead Strap, Chest Strap |



The veneral The veneral XAVIER THEVENARD XAVIER THEVENARD

CLIPLIGHT CU2R

SEE


AND

SEEN!

BE

TIP☆ The CU2R can be easily used as a **BACKLIGHT FOR MANY** headlamps for example e.g. HF-Series (p. 9) or NEO1R (p. 26)









CU2R is your trusted light partner that provides extra everyday safety in dim conditions and beyond – whether it's on a walk with the dog, on an evening run during rush hour or in everyday life as a rear light on clothing or backpack.

- 01 Compact, lightweight and versatile signal light with reflective wristband to increase safety in the dark
- 02 One white LED and two extra bright red LEDs offering two modes (power, blink)
- 03 Intuitive operation with two separate switches for white light and red light
- 04 Elastic strap with hook-and-loop closure and metal clip for quick and flexible attachment, e.g. on upper arm, clothing or backpack

KEY RING LIGHTS







K-SERIES



| | | K4R |
|------------|--|---|
| l | ED | |
| \frown | LED-Configuration | 1x Power LED |
| ull | Light Functions | Boost / Power / Low Power |
| Ķ- | Luminous Flux ¹ (lm) | 120 / 80 / 20 |
| ≓⊒∻ | Beam Distance ¹ (m) | 30 / 25 / 10 |
| ╚ | Run Time ¹ (h) | - / 1 / 3,5 |
| В | ATTERY AND CASE | |
| IIII) | Battery | 1x Li-ion Akku 3,7V |
| III) | Battery Capacity ² (Wh / mAh) | 0,67 / 180 |
| Ô | Rechargeable | Yes |
| Ġ | Charging Time ⁵ (min) | 180 |
| ÷ | IP Level | IP2X |
| S | IZE AND WEIGHT | |
| 2 | Length – Defocused (mm) | 52 |
| \bigcirc | Head Diameter (mm) | 25 |
| ß | Weight incl. Battery (g / oz) | 20 / 0,7 |
| F | EATURES | |
| | Standard-MODEL | Transportation Lock, Battery Indicator, Charge Indicator |
| P | ACKAGING | |
| | ltem no. Box / Rosé-Gold | Rose Gold: LL502575 / 4058205029148 |
| | Item no. Box / Gray | Gray: LL502574 / 4058205029117 |
| | | |

K6R (Rose Gold) + RED LIGHT K6R (Gray)



KIDSLIGHTS





KIDSLIGHTS LIGHT, FUN AND SAFETY

The Ledlenser KidsLights series lights specifically address the needs and requirements of children. They offer a wide range of uses, from the selfmade cave to the safe way to school, a multitude of colorful light functions, quick and easy operation, and practical energy-saving features. And, most importantly, safety always comes first. For instance, glaring effects and the luminous flux are reduced and all headlamps come with safety headbands which open automatically.



Versatile: white light, red light and blue light with optional flashing functions (red and blue)

Clever: Optics with reduced glaring for children's sensitive eyes

Energy-saving: automatic switch-off after 20 minutes (optional)



Practical: integrated metal clip for further attachment options without headband (e.g. on school satchel, backpack, clothing)

Safe: Pressure sensitive headband that releases automatically to prevent accidental injury





| LED | | |
|--|--|--|
| △ LED Configuration | 1x Power LED (White), 1x LED (Red), 1x LED (Blue) | 1x Power LED (White), 1x LED (Red), 1x LED (Blue) |
| 배비 Light Functions | Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue)) | Power (White), Low Power (White), (Power (Red), Blink (Red), Power (Blue), Blink (Blue), Blink (Red / Blue)) |
| -兴- Luminous Flux ¹ (lm) | 40 / 5 | 40 / 5 |
| □ → Beam Distance ¹ (m) | 9 / 2 | 9 / 2 |
| Bun Time ¹ (h) | 1.5 / 20 | 2 / 18 |
| BATTERY AND CASE | | |
| - Battery | 1 x AAA Alkaline 1.5V | 1 x Li-ion 3.7V (intern) |
| Battery Capacity ² (Wh / mAh) | | 1.036/280 |
| 📼 Rechargeable | No | Yes |
| © Charging Time⁵ (min) | | 60 |
| က် IP Level | IPX4 | IP56 |
| SIZE AND WEIGHT | | |
| Durchmesser (mm) | 54 | 37 |
| Weight incl. Battery (g / oz) | 35 / 1.2 | 25 / 0.9 |
| FEATURES | | |
| | White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light | White Light, Red Light, Blue Light, Automatic Switch-Off (optional), Safety Headband, Metal Clip for Mounting as Clip Light, Charge Indicator |
| PACKAGING (BOX) | | |
| Item no. / GTIN | LL502537 (Green) / 4058205027038 | LL502535 (Green) / 4058205026970 |
| Item no. / GTIN | LL502538 (Purple) / 4058205027069 | LL502536 (Purple) / 4058205027007 |
| Content Box | 1 Set of Batteries | Micro-USB Charging Cable |





KIDSLIGHTS




| | KIDBEAM4 [*] | KIDCAMP <mark>6</mark> * |
|--|--|---|
| LED | | |
| ☐ LED Configuration | 1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green) | 1x Power LED (White), 1x LED (Red), 1x LED (Blue), 1x LED (Green) |
| 메비 Light Functions | Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red und Blue)) | Power (White) / Low Power (White) (+ Power (Red), Power (Blue), Power (Green), Blink (Red, Blue und Green)) |
| -兴- Luminous Flux1 (lm) | 70 / 10 | 60 / 10 |
| ⊏]→ Beam Distance¹ (m) | 12 / 5 | -/- |
| Run Time ¹ (h) | 4 / 18 | 8 / 40 |
| BATTERY AND CASE | | |
| 📼 Battery | 2 x AAA Alkaline 1.5V | 3 x AAA Alkaline 1.5V |
| Battery Capacity ² (Wh / mAh) | | |
| 📼 Rechargeable | No | No |
| ট Charging Time⁵ (min) | _ | - |
| ငှာ IP Level | IP44 | IP44 |
| SIZE AND WEIGHT | | |
| O Durchmesser (mm) | 35 | 75 |
| 🖉 Weight incl. Battery (g / oz) | 72 / 2.5 | 95 / 3.4 |
| FEATURES | | |
| | White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Clip | White Light, Red Light, Blue Light, Green Light, Automatic Switch-Off (optional), Fold-Out Hook for Hanging Up the Light |
| PACKAGING (BOX) | | |

| Content Box | 1 set of batteries | 1 set of batteries |
|-----------------|-----------------------------------|-----------------------------------|
| | | |
| ltem no. / GTIN | LL502789 (Purple) / 4058205031653 | LL502786 (Purple) / 4058205031561 |
| Item no. / GTIN | LL502754 (Green) / 4058205030861 | LL502753 (Green) / 4058205030847 |
| PACKAGING (BOX) | | |

* Caution: Not suitable for children under 36 months. Caution: Use under direct adult supervision.









Exploring with your first own flashlight:

The robust Kidbeam4 lights up in four different colors and impresses with practical, child-specific features such as the integrated clip or the automatic switch-off function.



For cozy evenings of playing or reading: The Kidcamp6 provides the right mood and lights up in four different colors. It can be mounted in various ways thanks to the foldout hook, e.g. in a tent or caravan.

OUTDOOR LANTERNS





ML6 CONNECT WL Seable





•**:** 750 lm¹ – • 180 h¹ –



- 01 Micro Prism Technology patented⁴ lens technology for glare-free light and high energy efficiency
- 02 Ledlenser Connect App and wireless Bluetooth® remote control enable personalization and remote control of the light functions
- **03 Infinitely dimmable** via three-way switch
- **04 Powerbank function** with USB connection for charging electronic devices
- 05 Red light to maintain night vision ability
- O6 Rubber hook for hanging the light, integrated magnet for mounting it on metal surfaces, and a removable stand with a built-in metal hook that can be flipped out to provide more light mounting options
- 07 Convenient and safe charging via Magnetic Charge System
- **08** Integrated battery and charge status indicator

GLARE-FREE 360° ILLUMINATION WITH REMOTE CONTROL

Bluetooth[®]







LEDLENSER

- ML-SERIES

ML<mark>4</mark>





ML4 Warm Light

| LED | | |
|----------------------------------|--|--|
| △ LED Configuration | 9x Power LED, 9x LED Rot | 9x Power LED, 9x LED Rot |
| 메웨 Light Functions | Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot) | Boost / Power / Mid Power / Low Power (+ Blink, alle Light Functions auch in Rot) |
| | 300 / 150 / 50 / 5 | 300 / 150 / 50 / 5 |
| ⊐]→ Beam Distance¹ (m) | _ | _ |
| Bun Time ¹ (h) | - / 2.5 / 8 / 45 | - / 2.2 / 7 / 40 |
| BATTERY AND CASE | | |
| m Battery | 1x 14500 Li-ion Battery 3.7V | 1x 14500 Li-ion Battery 3.7V |
| 🗈 🛛 Battery Capacity² (Wh / mAh) | 2.77 / 750 | 2.77 / 750 |
| D Rechargeable | Yes | Yes |
| ⊙ Charging Time⁵ (min) | 150 | 150 |
| က္ IP Level | IP66 | IP66 |
| SIZE AND WEIGHT | | |
| 💭 Diameter (mm) | 34.5 | 34.5 |
| ✓ Height (mm) | 97 | 97 |
| g Weight incl. Battery (g / oz) | 71 / 2.5 | 71 / 2.5 |
| TECHNOLOGY | | |
| 🗊 Micro Prism Technology | • | • |
| J Temperature Control | • | • |
| Powerbank Function | | |
| Magnetic Charge System | • | • |
| Dual Power Source | • | • |
| More Features | Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light | Low Battery Warning, Charge Indicator, Battery Indicator, Transportation Lock, Red Light |
| PACKAGING | | |
| Item no. Window Box / GTIN | LL502053 / 4058205017886 | LL502231 / 4058205022125 |
| Content Box | 1 Set of Batteries, Magnetic Charging Cable | 1 Set of Batteries, Magnetic Charging Cabl |

| iŀ | DESIGN AWARD 2019 | PRODUCT WIDEO | |
|----|-------------------------|---------------|--|
| | | of geable | |

| PRODUCT VUED | PRODUCT VIDED | PRODUCT VIDEO |
|---|---|---|
| ML6 | ML6 Warm Light | ML6 Connect WL |
| | | |
| 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot |
| Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Mid Power / Low Power (+ Blink, Pulse, Position, Strobe, S.O.S., Alpine emergency signal, all functions also in red) |
| 750 / 550 / 5 | 750 / 550 / 5 | 750 / 550 / 100 / 5 |
| | _ | |
| - / 4 / 240 | - / 3.5 / 200 | |
| | | |
| 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V |
| 10,89 / 3000 | 10.89 / 3000 | 10.89 / 3000 |
| Yes | Yes | Yes |
| 300 | 300 | 300 |
| IP66 | IP66 | IP66 |
| | | |
| 42 | 42 | 45 |
| 178 | 178 | 178 |
| 280 / 9.9 | 280 / 9.9 | 260 / 9.2 |
| | | |
| • | • | • |
| • | • | • |
| • | • | • |
| | - | • |
| Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Bluetooth®, Memory Mode, Emergency Light |
| | | |
| LL500929 / 4058205011259 | LL502084 / 4058205017916 | LL502201 / 4058205021203 |
| 1 Set of Batteries, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batteries, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batteries, Stand, Transport Bag, Magnetic Charging Cable |

| DESIGN 2019 ROULT VIDEO ROULT VIDEO | RODUCT VIDEO | RODUCT VIDEO PRODUCT VIDEO |
|---|---|---|
| ML <mark>6</mark> | ML6 Warm Light | ML6 Connect WL |
| | 3 | |
| 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot | 18x Power LED, 6x LED Rot |
| Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Low Power (+ Blink, Pulse, S.O.S., Strobe, all functions also in red) | Boost / Power / Mid Power / Low Power (+ Blink, Pulse, Position, Strobe, S.O.S., Alpine emergency signal, all functions also in red) |
| 750 / 550 / 5 | 750 / 550 / 5 | 750 / 550 / 100 / 5 |
| - | | - |
| -/ 4/240 | - / 3.5 / 200 | - / 3.5 / 12 / 180 |
| | | |
| 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V | 1x 18650 Li-ion Battery 3.6V |
| 10,89 / 3000 | 10.89 / 3000 | 10.89 / 3000 |
| Yes | Yes | Yes |
| 300 | 300 | 300 |
| IP66 | IP66 | IP66 |
| | | |
| 42 | 42 | 45 |
| 178 | 178 | 178 |
| 280 / 9.9 | 280 / 9.9 | 260 / 9.2 |
| | | |
| • | • | • |
| • | • | • |
| • | • | • |
| | | - |
| Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Memory Mode | Low Battery Warning, Charge Indicator, Battery Indicator, Dimmable, Transporta- tion Lock, Red Light, Bluetooth®, Memory Mode, Emergency Light |
| | | |
| LL500929 / 4058205011259 | LL502084 / 4058205017916 | LL502201 / 4058205021203 |
| 1 Set of Batteries, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batteries, Stand, Transport Bag, Micro-USB Cable | 1 Set of Batteries, Stand, Transport Bag, Magnetic Charging Cable |

44

PORTABLE ENERGY FLEX-SERIES





Nasualida (

FLEX-SERIES: THE FUTURE OF PORTABLE ENERGY

| FOR 21700 BATTERIES FLEX5 FLEX10 TECHNICAL SPECS Powerbank+ Powerbank+ Length (mm) 103 120 Widht (mm) 41 54 Height (mm) 28 29 Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 12 / 200 126 / 4.4 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 12 / 200 12 / 200 Battery 1x 21700 14 / 5.8 TECHNOLOGY 14.0 24.0 Prechargeable Yes Yes Ocharging Time ⁶ (min) 14.0 24.0 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning FEATURES 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Proserbark with replaceable battery 2. IP65 - water and dust protection a. Battery Charge (up to 30.% shorter charging time - compared to charging in a PTR CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 2. Safe Battery Storage | |
|--|---------------|
| FOR 21700 BATTERIES FLEX5 FLEX10 TECHNICAL SPECS Powerbank+ Powerbank+ 1 Length (mm) 103 120 > Width (mm) 41 54 Height (mm) 28 29 △ Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 △ Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 20 22 / 100 Li-ion Battery 3.7V > Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V > Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 > IP Level IP65 IP65 > Rechargeable Yes Yes > Charging Time ⁶ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Charge Indicator, Low Battery Warning FEATURES 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 0. IP65 – water and dust protection against short circuit (box and battery) 2. IP65 – water and dust protection against short circuit (box and battery) 3. Battery Charge Indicator for both batteries 0. Battery Charge Indicator Safe Battery Storage 5. Double protec | |
| TECHNICAL SPECS Powerbank+ Powerbank+ Length (mm) 103 120 Width (mm) 41 54 Height (mm) 28 29 Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY Image: Comparison of the second of the s | PRODUCT VIDEO |
| Length (mm) 103 120 Width (mm) 41 54 Height (mm) 28 29 Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight with Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 128 22 Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning FEATURES 6-IN-1 - - 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 - water and dust protection 3. Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 3. Battery Charge Indicator for both batterion 6. Double protection against short circuit (| |
| Width (mm) 41 54 Height (mm) 28 29 Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 164 / 5.8 164 / 5.8 Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁶ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning FEATURES 6-IN-1 -1 Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 2. IP65 – water and dust protection a P7R CORE / WORK / SIGNATURE) 5. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 4. Safe Battery Charge Indicator 6. Battery Charge Indicator 6. Battery Charge Indicator for both batteries 5. Double pro | |
| Height (mm) 28 29 Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 164 / 5.8 Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 - water and dust protection 3. Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 2. IP65 - water and dust protection a P7R CORE / WORK / SIGNATURE) 5. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 6. Battery Charge Indicator 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator for both batteries | |
| Weight with Battery (g / oz) 126 / 4.4 235 / 8.3 Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 FECHNOLOGY 12 2700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity2 (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging time – compared to charging time – compared to charging time – and dust protection 3. Battery CORE / WORK / SIGNATURE) 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 5. Battery Charge Indicator for both batteries MATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| Weight without Battery (g / oz) 55 / 1.9 164 / 5.8 TECHNOLOGY 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery 1x 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ^s (min) 140 240 Energy Status Battery Indicator, Low Battery Warning Battery Indicator, Low Battery Warning Dewerbank with replaceable battery EATURES 6-IN-1 - ONerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 - water and dust protection 3. Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 4. Safe Battery Charge Indicator 4. Safe Battery Charge Indicator 6. Battery Charge Indicator for both batteries 4. Safe Battery Charge Indicator for both batteries | |
| TECHNOLOGY Ix 21700 Li-ion Battery 3.7V 2x 21700 Li-ion Battery 3.7V Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning FEATURES 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 3. Battery Charge Indicator 4. Safe Battery Charge Indicator 6. Battery Charge Indicator 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator for both batteries MATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| Battery1x 21700 Li-ion Battery 3.7V2x 21700 Li-ion Battery 3.7VBattery Capacity² (Wh / mAh)16.65 / 450033.30 / 9000IP LevelIP65IP65RechargeableYesYesCharging Time ⁵ (min)140240Energy StatusBattery Indicator, Charge Indicator, Low Battery WarningBattery Indicator, Low Battery WarningEATURES6-IN-16-IN-11. Powerbank with replaceable battery1. Powerbank with replaceable battery1. Powerbank with replaceable battery2. IP65 - water and dust protection 3. Battery Charge (up to 30 % shorter charging time - compared to charging i a P7R CORE / WORK / SIGNATURE)1. Powerbank with replaceable battery4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator4. Safe Battery StorageMATCHESMTR Core, H7R Signature,H7R Core, H7R Signature, | |
| Battery Capacity ² (Wh / mAh) 16.65 / 4500 33.30 / 9000 IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator for both batteries 4ATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| IP Level IP65 IP65 Rechargeable Yes Yes Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 - water and dust protection 3. Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator for both batteries MATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| Rechargeable Yes Charging Time ^s (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 - water and dust protection 3. Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 3. Battery Storage 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 4. Safe Battery Storage 4. Safe Sattery Charge Indicator 6. Battery Charge Indicator for both batteries 6. Battery Charge Indicator for both batteries | |
| Charging Time ⁵ (min) 140 240 Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 3. Battery Charge Indicator 6. Battery Charge Indicator 6. Battery Charge Indicator for both batteries 4. Safe Battery Charge Indicator for both batteries | |
| Energy Status Battery Indicator, Charge Indicator, Low Battery Warning Battery Indicator, Charge Indicator, Low Battery Warning EATURES 6-IN-1 I. Powerbank with replaceable battery 6-IN-1 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 1. Powerbank with replaceable battery 2. IP65 – water and dust protection 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 1. Powerbank with replaceable battery 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 3. Battery Charge Indicator 4. Safe Battery Charge Indicator 6. Battery Charge Indicator for both batteries 4. Safe Core, H7R Signature, H7R Core, H7R Signature, | |
| Powerbank with replaceable battery IP65 - water and dust protection Battery Charger (up to 30 % shorter charging time - compared to charging in a P7R CORE / WORK / SIGNATURE) Safe Battery Storage Double protection against short circuit (box and battery) Battery Charge Indicator MATCHES Powerbank with replaceable battery IP65 - water and dust protection Battery Charge Indicator Powerbank with replaceable battery IP65 - water and dust protection Battery Charge Indicator Safe Battery Storage Double protection against short circuit (box and battery) Battery Charge Indicator Battery Charge Indicator for both batteries | |
| 1. Power bank with replaceable battery battery 2. IP65 – water and dust protection Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) Battery Charger (up to 30 % s charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 4. Safe Battery Storage Double protection against short circuit (box and battery) Safe Battery Storage 5. Double protection against short circuit (box and battery) Double protection against short circuit (box and battery) Battery Charge Indicator 4. Safe Dattery Charge Indicator H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| IP65 – water and dust protection Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) Safe Battery Storage Double protection against short circuit (box and battery) Battery Charge Indicator Battery Charge Indicator for both batteries | <u>}</u> |
| 3. Battery Charger (up to 30 % shorter charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 3. Battery Charger (up to 30 % softer charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 3. Battery Charger (up to 30 % softer charging time – compared to charging in a P7R CORE / WORK / SIGNATURE) 3. Battery Charger (up to 30 % softer charging time – compared to charging | ction |
| 4. Safe Battery Storage 4. Safe Battery Storage 5. Double protection against short circuit (box and battery) 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 6. Battery Charge Indicator for both batteries MATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, H7R Core, H7R Signature, | charging in |
| 5. Double protection against short circuit (box and battery) 5. Double protection against short circuit (box and battery) 5. Double protection against short circuit (box and battery) 6. Battery Charge Indicator 6. Battery Charge Indicator for both batteries 1ATCHES H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| MATCHES both batteries H7R Core, H7R Signature, H7R Core, H7R Signature, | ort |
| H7R Core, H7R Signature, H7R Core, H7R Signature, | |
| | |
| P7R Core, P7R Signature P7R Core, P7R Signature | |
| PACKAGING | |
| Item no. Box / GTIN LL502511 / 4058205026697 LL502127 / 4058205019286 | |
| Content1 Rechargeable Battery, USB Cable (USB-A to USB-C)2 Rechargeable Batteries, USB (USB-A to USB-C) | Cable |



















Innovative 6-in-1-System

Flexible, sustainable, powerful – that distinguishes our new Flex series; the ideal addition for all outdoor activities. The rechargeable batteries of the new Ledlenser powerbanks can be removed at any time and are easy to swop out after being drained.

Therefore, the powerbanks can charge the 18650 respectively 21700 batteries used in compatible Ledlenser lights and in other electronic devices.

....

+-----



(USB Type-A to Type-C) Micro-USB cable included

FLEX-SERIES: EVEN MORE POWER ON THE GO

| • FOR 18650 BATTERIES | | |
|--|--|--|
| | FLEX3 | FLEX7 |
| TECHNICAL SPECS | Powerbank+ | Powerbank+ |
| Length (mm) | 109 | 109 |
| → Width (mm) | 27 | 47 |
| 🕽 Height (mm) | 27 | 27 |
| Weight with Battery (g / oz) | 88 / 3.1 | 164 / 5.8 |
| o g Weight without Battery (g / oz) | 40 / 1.4 | 116 / 4.1 |
| TECHNOLOGY | | |
| ■ Battery | 1x 18650 Li-ion Battery 3.6V | 2x 18650 Li-ion Batteries 3.6V |
| Battery Capacity ² (Wh / mAh) | 12.34 / 3400 | 24.68 / 6800 |
| ာ IP Level | IP65 | IP65 |
| Rechargeable | Yes | Yes |
| ற் Charging Time⁵ (min) | 240 | 240 |
| Energy Status | Battery Indicator, Charge Indicator, Low Battery Warning | Battery Indicator, Charge Indicator, Low Battery Warning |
| FEATURES | 6-IN-1 | 6-IN-1 |
| | Powerbank with replaceable battery | 1. Powerbank with replaceable battery |
| | 2. IP65 – water and dust protection | 2. IP65 – water and dust protection |
| | Battery Charger (up to 30 % shorter charging time – compared to charging in a P6R CORE / WORK / SIGNATURE) | Battery Charger (up to 30 % shorter charging time – compared to charging in a P6R CORE / WORK / SIGNATURE) |
| | 4. Safe Battery Storage | 4. Safe Battery Storage |
| | Double protection against short circuit (box and battery) | Double protection against short circuit (box and battery) |
| | 6. Battery Charge Indicator | Battery Charge Indicator for both batteries |
| MATCHES | | |
| | | |
| | P6R Core, P6R Signature, MH11, ML6 Series | P6R Core, P6R Signature, MH11, ML6 Series |
| PACKAGING | | |
| Item no. Box / GTIN | LL502126 / 4058205019255 | LL502125 / 4058205019224 |
| Contents Box | 1 Rechargeable Battery, Micro-USB Cable | 2 Rechargeable Batteries, Micro-USB Cable |









FLASHLIGHTS





— P-SERIES CORE



| | D2D CODE | Comments and the second |
|--|---|--------------------------------|
| | P2R CORE | P <mark>3</mark> CORE |
| LED | | |
| △ LED Configuration | 1x Power LED | 1x Power LED |
| 배에 Light Functions | Power / Mid Power / Low Power | Power / Mid Power / Low Power |
| -兴- Luminous Flux1 (lm) | 120 / 50 / 15 | 90 / 50 / 15 |
| ⊐ → Beam Distance ¹ (m) | 65 / 45 / 15 | 110 / 70 / 40 |
| Run Time ¹ (h) | 0.5 / 1 / 5 | 3/4/6 |
| ^{[]K} Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| (R) Color Rendering Index (CRI) | 70 | 70 |
| BATTERY AND CASE | | |
| | 1x Li-ion Battery 3.7V with Micro-US | B 1x Micro (AAA) Alkaline 1.5V |
| 📼 Battery Capacity² (Wh / mAh) | 0.74 / 200 | |
| 🕂 IP Level | IP54 | IP54 |
| (j) Rechargeable | Yes | No |
| Ē Charging Time⁵ (min) | 150 | |
| | 2 | 2 |
| SIZE AND WEIGHT | | |
| ∠ [¬] Length – Defocused (mm) | 103 | 96 |
| 🔘 Head Diameter (mm) | 15 | 20 |
| Weight incl. Battery (g / oz) | 36 / 1.3 | 42 / 1.5 |
| TECHNOLOGIE | | |
| 🚻 Smart Light Technology | | |
| 🔅 Flex Sealing Technology | | |
| 💿 Magnetic Charge System | | - |
| Temperature Control | | - |
| Advanced Focus System | • | • |
| More Features | Energy Saving | Rapid Focus |
| PACKAGING | | |
| ltem no. Box / GTIN | LL502176 / 4058205020367 | LL502597 / 4058205028462 |
| Content Box | 1 Battery Set, Pocket Clip, Micro-USB Charging Cable | 1 Battery Set, Pocket Clip |

| 0 | 0 |
|-------------------------------|--------------------------|
| P4 CORE | P <mark>4R</mark> CORE |
| | |
| 1x Power LED | 1x Power LED |
| Power / Mid Power / Low Power | Power / Mid Power / Lo |
| 120 / 60 / 15 | 200 / 90 / 15 |
| 90 / 55 / 25 | 90 / 60 / 15 |
| 5 / 9 / 20 | 1.5 / 3 / 25 |
| 6000 - 7500 | 6000 - 7500 |
| 70 | 70 |
| | |
| 2x Micro (AAA) Alkaline 1.5V | 1x Li-ion Battery Pack 3 |
| | 2.22 / 600 |
| IP54 | IP54 |
| No | Yes |
| | 150 |
| 2 | 2 |
| | |
| 146 | 150 |
| 15 | 15 |
| 58 / 2.0 | 55 / 1.9 |
| | |
| | |
| | |
| | |
| | |
| • | • |
| | Energy Saving |
| | |
| LL502598 / 4058205028493 | LL502177 / 405820502 |
| | |

1 Battery Set, Pocket Clip

1 Battery Set, Pocket Clip, Micro-USB Charging Cable



ow Power

k 3.7V

020398



— P-SERIES CORE

| | P5 CORE | P5R CORE |
|---|--------------------------------|---|
| LED | | |
| ❑ LED Configuration | 1x High Power LED | 1x High Power LED |
| III Light Functions | Power / Mid Power / Low Power | Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe) |
| Ų́- Luminous Flux¹(lm) | 150 / 60 / 15 | 500 / 350 / 130 / 15 |
| ⊲T→ Beam Distance¹ (m) | 90 / 60 / 30 | 250 / 180 / 110 / 40 |
| D Run Time ¹ (h) | 2.5 / 5 / 12 | - / 1 / 3.5 / 25 |
| ^{IIK} Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| Color Rendering Index (CRI) | 70 | 70 |
| BATTERY AND CASE | | |
| Battery | 1x Mignon (AA) Alkaline 1.5V | 1x 14500 Li-ion Battery 3.7V |
| Battery Capacity² (Wh / mAh) | | 2.77 / 750 |
| P IP Level | IP44 | IP68 |
|) Rechargeable | No | Yes |
| Charging Time⁵ (min) | | 120 |
| Drop Height (m) | 2 | 2 |
| SIZE AND WEIGHT | | |
| Length – Defocused (mm) | 120 | 123 |
|) Head Diameter (mm) | 26 | 29 |
| 9 Weight incl. battery (g / oz) | 83 / 2.9 | 106 / 3.7 |
| TECHNOLOGY | | |
| Smart Light Technology | | • |
| Flex Sealing Technology | | • |
| Magnetic Charge System | | • |
| J Temperature Control | | • |
| Advanced Focus System | • | • |
| More Features | Dual Power Source, Rapid Focus | Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning |

red<mark>dot</mark> winner 2021

reddot winner 2021

| PACKAGING | | |
|---------------------|--------------------------|--|
| ltem no. Box / GTIN | LL502599 / 4058205028523 | LL502178 / 4058205020428 |
| Content Box | 1 Battery Set, Lanyard | 1 Battery Set, Lanyard, Magnetic Charging Cable |

| eddot win | ner 2021 reddot w |
|------------------------------|---|
| A sub- | |
| P <mark>6</mark> CORE | P6R CORE |
| | |
| 1x High Power LED | 1x Xtreme LED |
| Power / Low Power | Boost / Power / Mid Power / L (+ Position, Blink, S.O.S., Strobe |
| 300 / 25 | 900 / 600 / 240 / 15 |
| 200 / 60 | 240 / 190 / 120 / 25 |
| 3.5 / 25 | - / 2 / 6 / 95 |
| 6000 - 7500 | 6000 - 7500 |
| 70 | 65 |
| | |
| 3x Micro (AAA) Alkaline 1.5V | 1x18650 Li-ion Battery 3.7V |
| | 9.25 / 2500 |
| IP54 | IP68 |
| No | Yes |
| | 300 |
| 2 | 2 |
| | |
| 117 | 151 |
| 32 | 35 |
| 130 / 4.6 | 170 / 6.0 |
| | |
| | • |
| | • |
| | • |
| | • |
| • | • |
| Energy Saving, Rapid Focus | Dimmable, Transportation Loo Flicker-free, Memory Mode, Ba Emergency Light, Temperatur System, Battery Indicator, Cha Indicator, Low Battery Warnin |
| | |
| LL502600 / 4058205028554 | LL502179 / 4058205020459 |
| 1 Battery Set, Lanyard | 1 Battery Set, Lanyard, Magnetic Charging Cable |

| 2 |
|--|
| reddot winner 2021 |
| - Long |
| able . |
| Lechon de la constante de la c |
| |
| |
| wer / Low Power ., Strobe) |
| |
| |
| |
| |
| |
| / 3.7V |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| tion Lock, ode, Backup Mode, perature Control tor, Charge |
| Warning |
| |

P<mark>5R</mark> CORE

The state

6

10

05

02 03

- 01 Extreme dust and water predection (IP68)
- 02 Advanced Focus System stepless focusing
- 03 Flex Sealing Technology – can be used for a short time underwater (including the focusing system) to a depth of one meter
- **04** Personalize the light functions via Smart Light Technology
- **05** Convenient and safe charging the battery thanks to the Magnetic Charge System
- 06 Constant Light constant luminous flux over a long period
- 07 Flicker-free constant light enables optimal and safe illumination

A TIMELESS CLASSIC

- P7R CORE











- 01 Extreme dust and water prodection (IP68)
- 02 Advanced Focus System stepless focusing
- **03 Flex Sealing Technology** can be used for a short time underwater (including the focusing system) to a depth of one meter
- **04 Multi-Core Optics** homogeneous beam made possible by special faceting of the lens
- **05** Personalize the light functions via Smart Light Technology
- 06 Integrated Battery and Charge Status Display
- **07** Convenient and safe charging of the battery thanks to the Magnetic Charge System







- P-SERIES CORE



| LED | | | | |
|----------------|---|--|--|--|
| \Box | LED Configuration | | | |
| ull | Light Functions | | | |
| -ờ́- | Luminous Flux ¹ (lm) | | | |
| ⇒ | Beam Distance ¹ (m) | | | |
| ╚ | Run Time ¹ (h) | | | |
| ₿ ^ĸ | Color Temperature (K) | | | |
| (CRI) | Color Rendering Index (CRI) | | | |
| В | ATTERY AND CASE | | | |
| E COMP | Battery | | | |
| me) | Battery Capacity ² (Wh / mAh) | | | |
| Ġ | IP Level | | | |
| Ŷ | Rechargeable | | | |
| Ō | Charging Time⁵ (min) | | | |
| <u>+</u> | Drop Height (m) | | | |
| S | IZE AND WEIGHT | | | |
| 2 | Length – Defocused (mm) | | | |
| \bigcirc | Head Diameter (mm) | | | |
| ß | Weight incl. Battery (g / oz) | | | |
| Т | ECHNOLOGY | | | |
| | Smart Light Technology | | | |
| | Flex Sealing Technology | | | |
| 00 | Magnetic Charge System | | | |
| | Multi Core Optics | | | |
| | Advanced Focus System | | | |
| | More Features | | | |
| | Battery Capacity ² (Wh / mAh) IP Level Rechargeable Charging Time ⁵ (min) Drop Height (m) IZE AND WEIGHT Length – Defocused (mm) Head Diameter (mm) Weight incl. Battery (g / oz) ECHNOLOGY Smart Light Technology Flex Sealing Technology Magnetic Charge System Multi Core Optics Advanced Focus System | | | |

| P7 CORE | P7R CORE |
|-------------------------------|-----------------------|
| | |
| 1x Power LED | 1x Xtreme LED |
| Power / Mid Power / Low Power | Boost / Power / Mid F |

Y

red<mark>dot</mark> winner 2021

| 1x Power LED | 1x Xtreme LED | 1x Xtreme LED |
|-------------------------------|--|---|
| Power / Mid Power / Low Power | Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe) | Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe) |
| 450 / 250 / 40 | 1400 / 1000 / 440 / 15 | 1200 / 900 / 350 / 15 |
| 300 / 220 / 100 | 300 / 210 / 130 / 15 | 560 / 420 / 270 / 50 |
| 1 / 2 / 25 | - / 2 / 4 / 90 | - / 2.75 / 12 / 200 |
| 6000 - 7500 | 6000 - 7500 | 6000 - 7500 |
| 70 | 70 | 65 |
| | | |
| 4x Micro (AAA) Alkaline 1.5V | 1x 21700 Li-ion Battery 3.7V | 1x LiFePO4 Battery pack 6.4V |
| | 17.76 / 4800 | 36.48 / 5700 |
| IP54 | IP68 | |
| No | Yes | Yes |
| | 270 | 270 |
| 1 | 2 | 1 |
| | | |
| 130 | 158 | 290 |
| 37 | 35 | 53 |
| 175 / 6.2 | 202 / 7.1 | 715 / 25.2 |
| | | |
| | • | • |
| | • | |
| | • | • |
| | • | |
| • | • | • |
| Energy Saving, Rapid Focus | Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Temperature Control System, Battery Indicator, Charge Indicator, Low Battery Warning | Mode Switch, Dimmable, Transportation Lock, Flicker-free, Memory Mode, Backup Mode, Emergency Light, Safety Ytrion Ce Rapid Focus, Battery Indicator, Charge Indicator, Low Battery Warning |
| | | |
| LL502180 / 4058205020480 | LL502181 / 4058205020510 | LL502182 / 4058205020541 |
| 1 Battery Set, Lanyard | 1 Battery Set, Lanyard, Magnetic Charging Cable | – 1 Set of Batteries, Intelligent Clip, Wall Mount, Power Adapter, Magnetic Charging Cable |

Content Box

PACKAGING

Item no. Box / GTIN

| PRODUCT NOT CONTRACT OF CONTRACT. | ACM-11 | |
|---|--------|--|
| | | |



P17R CORE

towner the





01 – Equipped with a Multicolor LED with white, red, green and blue light

02 - Multicolor Strobe colored flashes of light with irritating glare effect for emergencies

- 03 Easy Operation the rotary switch enables quick color changes
- 04 Advanced Focus System stepless focusing





P6R CORE QC

| LED | |
|----------------------------------|---|
| △ LED Configuration | 1x Power LED |
| I Light Functions (weißes Licht) | Power / Mid Power / Low Power |
| -兴- Luminous Flux1 (lm) | 270 / 120 / 15 |
| ⊏]→ Beam Distance¹ (m) | 335 / 220 / 80 |
| Run Time ¹ (h) | 5 / 14 / 110 |
| | 6000 - 6500 |
| (R) Color Rendering Index (CRI) | 80 (white light) |
| BATTERY AND CASE | |
| 🞰 Battery | 1x Li-ion Battery 3.7V |
| 📼 Battery Capacity² (Wh / mAh) | 9.25 / 2500 |
| ငှိ IP Level | IP54 |
| 🖞 Rechargeable | Yes |
| টি Charging Time⁵ (min) | 300 |
| ↓ Drop Height (m) | 1.5 |
| SIZE AND WEIGHT | |
| 고 Length – Defocused (mm) | 157 |
| 🔘 Head Diameter (mm) | 42 |
| 🖉 Weight incl. Battery (g / oz) | 207 / 7.3 |
| TECHNOLOGY | |
| Rapid Focus | • |
| 🚭 Advanced Focus System | • |
| More Features | Multicolor Strobe, Singlecolor Strobe |
| PACKAGING | |
| ltem no. Box / GTIN | LL502517 / 4058205026819 |
| Content Box | 1 Battery Set, Lanyard, Micro-USB Charging Cable |





SEEING THE WORLD IN A DIFFERENT LIGHT

| REEN | BLUE |
|--|---|
| ildlife watching: een light is almost visible to animals | Forensic analysis: liquids appear with higher contrast |
| ver / Mid Power / Low Power | Power / Mid Power / Low Power |
|) / 75 / 15 | 35 / 10 / 5 |
|) / 190 / 80 | 50 / 30 / 15 |
| 20 / 120 | 7 / 20 / 120 |

- P7R SIGNATURE

PREMIUM ILLUMINATION











01 – Powerful premium flashlight with Natural Light Technology (80 CRI / 6500K)

LEDLENSER PTR Signature

04

- **02 Mode Switch** for direct access to personalized light functions via Smart Light Technology
- 03 Additional red secondary light on the side of the housing, e. g. to maintain the night vision
- 04 Hard-anodized housing material for additional protection against wear and corrosion
- 05 Extreme dust and water protection (IP68)
- 06 Flex Sealing Technology can be used for a short time underwater (including the focusing system) to a depth of one meter
- **07** Personalize the light functions thanks to Smart Light Technology
- **08 Constant Light** consistent level of brightness over time
- 09 Integrated battery and charge status indicator









MAXIMUM PERFORMANCE, STYLISH DESIGN







P6R SIGNATURE

Y

Veddot winner 2020

| L | ED | | |
|-------------|--|--|--|
| \Box | LED Configuration | 1x Xtreme LED, (1x red LED) | 1x Xtreme LED, (1x red LED) |
| ull | Light Functions | | Boost / Power / Mid Power / Low Power (+ Position, Blink, S.O.S., Strobe, Red Light) |
| <u>-ờ́-</u> | Luminous Flux ¹ (lm) | 1400 / 1100 / 450 / 15 | 2000 / 1200 / 500 / 15 |
| ⊐⇒ | Beam Distance ¹ (m) | 240 / 190 / 110 / 20 | 330 / 200 / 130 / 20 |
| (| Run Time¹ (h) | - / 1.25 / 2.5 / 60 | - / 2 / 3.25 / 90 |
| βĸ | Color Temperature (K) | 6000 - 7500 | 6000 - 7500 |
| (R) | Color Rendering Index (CRI) | 80 | 80 |
| В | ATTERY AND CASE | | |
| (IIII) | Battery | 1x 18650 Li-ion Battery 3.6V | 1x 21700 Li-ion Battery 3.7V |
| | Battery Capacity ² (Wh / mAh) | 10.89 / 3000 | 17.76 / 4800 |
| Ġ | IP Level | IP68 | IP68 |
| Ŷ | Rechargeable | Yes | Yes |
| Ō | Charging Time ⁵ (min) | 225 | 270 |
| <u> </u> | Drop Height (m) | 2 | 2 |
| S | IZE AND WEIGHT | | |
| 2 | Length – Defocused (mm) | 151 | 158 |
| \bigcirc | Head Diameter (mm) | 35 | 35 |
| ൔ | Weight incl. Battery (g / oz) | 170 / 6.0 | 202 / 7.1 |
| Т | ECHNOLOGY | | |
| | Smart Light Technology | • | • |
| | Flex Sealing Technology | • | • |
| <u></u> | Magnetic Charge System | • | • |
| | Multi-Core Optics | • | • |
| | Advanced Focus System | • | • |
| | More Features | Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Char- ge Indicator, Low Battery Warning | Red Alternate Light, Mode Switch, Emergency Light, Temperature Control, Dimmable, Transportation Lock, Flicker- free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning |
| P | ACKAGING | | |
| | ltem no. Box / GTIN | LL502189 / 4058205020756 | LL502190 / 4058205020787 |
| | Content Box | 1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket | 1 Set of Batteries, Leather Belt Pouch, Lanyard, Magnetic Charging Cable, Pocket Clip, USB Power Adapter, Wall Bracket |



-/2.5/4.5/70

6000 - 7200

70

1x Li-ion Battery Pack 11.1V 33.3 / 3000 IP54 Yes 330 1 171 86 637 / 22.5

X-Lens Technology, Rapid Focus, Dimmable, Transportation Lock, Flicker-free, Memory Function, Backup Mode, Emergency Light, Battery Indicator, Charge Indicator, Low Battery Warning

LL502191 / 4058205020817

1Set of Batteries, Lanyard, USB Power Adapter, Magnetic Charging Cable

P-SERIES









02 03 06



01 - Staying Power - thanks to the front switch, the light can be set down and used as room lighting

01

- 02 Smart Light Technology easily be selected with your thumb via soft touch easily be selected with your thumb via soft touch
- 03 Battery Status and Charge Indicator located inside the front switch
- 04 Rapid Focus fast switching and focusing with only one hand
- **05 Advanced Focus System –** seamless focus feature of homogeneous, circular low beam (defocused) to a sharply bundled high beam (focused)
- 06 Transportation Lock light will not accidentally switch on in your bag



MT10

| L | ED | | |
|---------------|--|--|---|
| \Box | LED-Configuration | 1x Xtreme LED | 1x Xtreme LED |
| 411 | Light Functions | Power / Mid Power / Low Power (+ Strobe) | Power / Mid Power / Low Power (+ Strobe) |
| -ÿ. | Luminous Flux ¹ (lm) | 1000 / 200 / 10 | 1000 / 200 / 10 |
| ت | Beam Distance ¹ (m) | 180 / 100 / 20 | 320 / 120 / 30 |
| | Run Time ¹ (h) | 6 / 15 / 144 | 9 / 20 / 192 |
| В | ATTERY AND CASE | | |
| Ē | Battery | 1x 18650 Li-ion Battery 3,6V | 1x 26650 Li-ion Battery 3,7V |
| III- 1 | Battery Capacity ² (Wh / mAh) | 11,52 / 3200 | 18,13 / 4900 |
| Ô | Rechargeable | Yes | Yes |
| Þ | Charging Time⁵ (min) | 360 | 480 |
| Ġ | IP Level | IP54 | IP54 |
| S | IZE AND WEIGHT | | |
| 2 | Length – Defocused (mm) | 128 | 151 |
| \bigcirc | Head Diametre (mm) | 32 | 39 |
| ß | Weight incl. Battery (g / oz) | 156 / 5,5 | 253 / 8,9 |
| Т | ECHNOLOGY | | |
| | Smart Light Technology | • | • |
| ١ | Rapid Focus | • | • |
| | Advanced Focus System | • | • |
| | Temperature Control | • | • |
| | Features | Energy Saving, Constant Light, Charge Indi- cator, Battery Indicator, Transportation Lock | |
| P | ACKAGING | | |
| | Item no. Box / GTIN | LL500843 / 4058205007504 | LL500844 / 4058205007535 |

| PACKAGING | |
|---------------------|--|
| Item no. Box / GTIN | LL500843 / 405820500 |
| Contents | 1 Set of Batteries, Belt P Charging Cable, Pocket (|



Pouch, Lanyard, t Clip

1 Set of Batteries, Belt Pouch, Lanyard, Charging Cable

OUTDOOR & SPORTS ACCESSORIES HEADLAMPS

| MODEL | MH3 | MH4 | MH5 | MH7 | MH8 | ltem no. |
|-----------|-----|-----|-----|-----|-----|----------|
| Powercase | | • | • | • | • | 502093 |

POWERCASE Transport safely, charge conveniently

- Safe, secure transportation and protection for your headlamp
- Internal magnetic charging for compatible Ledlenser headlamps
- Powerbank (5,000 mAh) with USB-A connection
- Battery charging indicator

| Ν | ATCHES | WITH |
|---|--------|------|
| > | MH4 | |
| > | MH5 | |
| > | MH7 | |
| > | MH8 | |
| > | iH5R | |
| > | iH9R | |
| | | |

| POWERCASE | |
|----------------------------------|----------------------------|
| Weight incl. Battery (g) | 219 |
| Capacity ² (Wh / mAh) | 18,5 / 5000 |
| Charging Time⁵ (min) | 180 |
| ltem no. | 502093 |
| Contents | Snap hook, Micro-USB cable |





TECHNOLOGIES, ABOUT US, WARRANTY AND MORE





Ledlenser-Hauptsitz in Solingen

LEDLENSER **TECHNOLOGY ABC**

From innovative lenses and advanced light functions to future-oriented power supplies - we work tirelessly to improve our technology to further expand our lead. Here are some examples:



ACTIVE COOLING TECHNOLOGY

High luminosity requires special measures. A powerful fan

actively cools down the high-end LED and allows maximum light output over long periods of time – while remaining consistently

Our Adaptive Light Beam technology dims and focuses automatically. This way, the light is adapted to changing environments and obstacles; from uneven forest ground and wet sidewalks to narrow machine compartments – without manual control. The system detects blinding reflections as well as overall light conditions and controls all light sources separately. This does not only result in an ideal illumination and focusing, but it also enables completely hands-free use, with an extended battery runtime.





ADVANCED FOCUS SYSTEM (AFS)

Galileo swore by the power of lenses; Newton by the power of reflectors. We have simply combined the two Technologies - only better than anyone before. The result: our patented Advanced Focus System (AFS), which allows a seamless transition from homogeneous low beam to sharply focused high beam.



COOLING TECHNOLOGY

Cooling Technology (CT) ensures your head stays cool even when your light is at maximum power. Our CT products reduce LED heat to the optimal level by means of the intelligent use of cooling elements. This technology is also used to cool computer chips and ensures highly efficient use of energy, increased illuminating power, and especially long-lasting LEDs.

| ~ | |
|---|-------|
| | - 🍫] |
| | 2 |

DUAL POWER SOURCE

Our Dual Power Source allows you to use the full performance of your Ledlenser at any time – no matter what power source you have available. This technology recognizes the power source and you can therefore. You can therefore choose between the rechargeable Ledlenser battery or a disposable battery. Extremely practical for long trips without a power point.



EMERGENCY LIGHT


This feature turns your flashlight into an emergency light: If the power goes out while your Ledlenser is on the charging base, it will automatically turn on. So the light helps you find your way around, e. g. to the breaker panel.

DIGITAL ADVANCED FOCUS SYSTEM

energy-efficient.

Our patent-pending Digital Advanced Focus System (dAFS) allows a virtually seamless transition from homogeneous floodlight to focused spotlight. Its efficiency delights even experts. The technology enables a slim design, ideal lighting for different ranges and permanent peripheral vision.

(NEW)






FLOATING CHARGE SYSTEM

Grab-and-go wireless charging. The Floating Charge System is a wall-mounted magnetic charging system, getting the light ready to go with a simple flick of the wrist. It also offers USB charging with an adapter system that can be plugged into standard outlets or car lighters.













FLEX SEALING TECHNOLOGY

The innovative Flex Sealing Technology ensures that the electronic parts of the lamp head are completely sealed off, to protect against the penetration of water and dust. This flexible System is used. The focus can even be used underwater.





FUSION BEAM


By combining different LEDs and lenses, lights with Fusion Beam have a unique, application-optimized illumination. This simultaneously enables a homogenous close-up wide flood beam and sharply focused long-distance beam. The intensity of the flood and spot beams can be individually adjusted thanks to independent controls for each light source.





MAGNETIC CHARGE SYSTEM

With the Magnetic Charge System, the charging cable can quickly and easily be attached to the light. The connection for charging the battery is made via magnetic contacts. When the contacts approach each other, the charging cable automatically pairs with the light. The connection is automatically released under load.





RAPID FOCUS

When focusing or defocusing the flashlight or headlamp, the reflector lens moves in relation to the LED. To ensure this process is as quick and ergonomic as possible we developed Rapid Focus: a single-hand mechanism that allows the light beam to be adjusted as fast as lightning.



SAFETY YTRION CELL

Ledlenser's Safety Ytrion Cell is a special lithium iron phosphate battery with unique properties: The technology combines high energy density with superior durability and safety, even in rough use and adverse storage conditions.



SMART LIGHT TECHNOLOGY (SLT)

This innovation turns a Ledlenser into your personal lighting tool: A micro-controller allows individual ranges of functions to be programmed to different touch and switch combinations. That way, you always have the perfect light mode at hand.

| Ň | ŎŎĊ | 0 |
|---|-----|---|
| | | |

MULTI-CORE OPTICS

Multi-Core Optics harness and direct the light emitted from extremely powerful, next-generation LEDs. The special faceted lens tames and directs the light, resulting in a homogeneous beam and aesthetic illumination.





TEMPERATURE CONTROL

Our lights stay cool, even when they work hard. Thanks to the intelligent and fully automated temperature control, a Ledlenser never gets too hot, no matter how much it is used. This protects you from burns and the LED from overheating.



NATURAL LIGHT


In certain situations the perceived color of light differs. Ledlenser therefore not only supplies extremely bright, but also extremely natural (CRI) over 90. This ensures true color rendering, even in the deep red color range.





X-LENS TECHNOLOGY


This technology is an enhancement of the Advanced Focus System. It can merge virtually any number of reflector lenses and synchronizes their individual light beams into a perfect beam, resulting in a high-grade, homogeneous floodlight in unfocused mode and our most sharply focused high beam to date.



















IT TAKES EIGHT MINUTES FOR THE LIGHT OF THE SUN TO REACH THE EARTH – OURS ONLY TAKES THE PUSH OF A BUTTON

The sun and Ledlenser have something in common: We create light for the whole world! We are devoted to this task with all our energy and capability. The quality products made by Ledlenser prolong daylight and therefore, enable being active when dusk sets in or even during total darkness. They bring light into the darkest corners and in doing so, enable precise and professional work at any time.

WHAT DISTINGUISHES US

- One of the global market leaders in portable lights. That includes: Flashlights, headlamps, work lights, floodlights, lanterns, EX-protected lights
- > "German Engineering & Design": In-house development, production and quality assurance
- > Inventor of the trendsetting and patented³ Advanced Focus System
- > 7-year warranty⁴ for most products in connection with online registration
- More than 100 industrial property rights as well as more than 200 awards and prizes for our products
- > More than 650 employees worldwide
- Company-owned offices in Germany, China, USA, Yespan, Denmark, United Kingdom, Italy and Switzerland
- > Worldwide collaboration with more than 30 master distributors

OUR PRODUCTION PLANT IN CHINA

To ensure that our bright ideas see the light of day, we clearly divided up our tasks: "Engineered in Germany, produced in China". Our production expertise is concentrated at our location in Yangjiang, Guangdong. Every product is manufactured and tested here; from prototype to mass production.

The checklist for quality control includes 24 tests: Endurance, extreme temperatures, water, salt, impact, pressure and more - inspected and tested until the products have overcome all obstacles and meet our quality standards. Furthermore, it is important to us to take responsibility for our employees in China. We do this for example by building company housing and through our involvement in social and intercultural projects.



MORE THAN 20 YEARS OF EXPERTISE IN LIGHTING SOLUTIONS

When the two brothers Harald and Rainer Opolka from Solingen started out, they really didn't have much more than a garage, an old Atari computer, a set of tools, a drawing pad and around 1000 Deutschmarks of seed capital. Today, the former garage company of both the Ledlenser founders is an internationally operating company and one of the global market leaders in portable lights. The German Ledlenser brand conquered the flashlight market in the year 2000. The approach of equipping a flashlight with an LED instead of a bulb as a light source was absolutely visionary at that point in time. Millions of the "V8 Photon Pump" were sold worldwide and it constituted a new era of portable light – the "P7" achieved the same thing several years later.

To meet our objective as an LED pioneer, we are still using this technological advantage today in the development of new products – particularly in times during which LED lighting has become the norm in so many places and genuine quality is becoming harder and harder to recognize. At the same time, our premise "German Engineering & Design" has guided us from day one and justifies our unique commitment to quality. Ledlenser products give users worldwide the freedom of doing their jobs to the best of their ability or pursuing their passion with devotion – with the best possible light on their side.

LEDLENSER **GUARANTEED QUALITY**



GERMAN ENGINEERING & DESIGN



Management ISO 9001:2015 ISO 14001:2015 ISO 50001:2018

QUALITY

"German Engineering & Design" - this statement stands for the highest development and production standards in regard to technology, design, materials and workmanship. We hold more than 100 industrial property rights. These include patents, utility models and designs. We are proud of having received various design awards for our products.

WARRANTY

Since we are confident in the quality of our lights, we grant a seven-year warranty on nearly all products in connection with online registration. All original Ledlenser products covered by our warranty include a product registration card. To register, simply scan the QR code with a smartphone or enter the indicated URL on your laptop or PC.

ISO CERTIFICATION

We meet the requirements of the ISO 9001, ISO 14001 and ISO 50001 standards and are certified by TÜV Rheinland.

Quality management: DIN EN ISO 9001:2015

Our systematic quality management ensures a consistently high quality of our products and services. Clearly defined and comprehensible processes enable us to meet our customers' expectations consistently and professionally. We also meet the standard requirements at our Chinese location.

Environmental management: DIN EN ISO 14001:2015

Our company has defined an internal environmental policy and precise environmental objectives. Here, the focus is on the establishment and realization of an environmental management system, to ensure continuous improvements – e. g. in regard to CO_2 emissions, the use of resources and other environmental factors.

Energy management: DIN EN ISO 50001:2018

We operate energy management geared towards sustainability. This includes measures to reduce the consumption of energy such as electricity, gas and fuel as well as specific risk prevention.



Contact Details

Burton McCall Limited 163 Parker Drive, Leicester, LE4 0JP

Tel Main Switchboard: 0116 234 4600

www.burton-mccall.co.uk

f @BTNMCCALL ②@burtonmccallItd **in**@burton-mccall-limited

Sales Office Tel: 0116 234 4611/4622 Email: sales@burton-mccall.com

Customer Services

Tel: 0116 234 4646 Email: customer.services@burton-mccall.com

