## EXTERIOR WOOD SEALER

A non-toxic sealer that will protect the exterior of wood while still allowing it to breathe as it dries. It is strong enough to prevent the wood stabilizers, Pentacryl, Wood Juice and Log & Beam Treatment, from leaching out of the wood, yet gentle enough to still allow the wood to dry and not trap the moisture inside.

Great for use on outdoor wood carvings, wood furniture, log, beam or timber home siding and other exterior wood items.

Exterior Wood Sealer dries clear and contains a UV protectant to help prevent sun fading and keep your wood looking new.

**Directions:** Using a paint brush, roller or sprayer, apply a generous coat of Exterior Wood Sealer to all surfaces of the wood. Let it dry several hours or overnight and apply a second coat.

For best penetration, apply Exterior Wood Sealer at temperatures above 50 degrees F.

Up to 3 coats may be applied if needed. The wood will only require one application per year for maintenance.

One gallon will treat approximately 50-75 square surface feet.

Contains no VOCs
Clean up with soapy water. Avoid contact with skin and eyes and use proper eye protection.

Keep out of the Reach of Children

Manufactured in the USA by:

## PRESERVATION SOLUTIONS, LLC

Golden, CO 80403

Ph: 303.642.3060 Fax: 303.648.6486 www.preservation-solutions.com