

BRICK SLIP | RECLAIMED COLLECTION

Blend 9

PRODUCT TECHNICAL INFORMATION SHEET

Belgium/UK
Cut Brick Slip
Yellow Multi
Tumbled
215 x 22* x 65
60
TBC

TECHNICAL PROPERTIES TO BS EN 771-1

TECHNICAL PROPERTIES TO B	3 LN //1-1
SIZE TOLERANCE (mean/range)	Tm/Rm
GROSS DRY DENSITY (kg/m3/tolerance)	1500 (D1)
COMPRESSIVE STRENGTH (N/mm2)	NPD
THERMAL CONDUCTIVITY (W/(m·K)) λ10, dry, unit value (EN 1745 tabulated: S1)	P=90% 0.51
DURABILITY DESIGNATION	F2
WATER ABSORPTION (%)	≤22
INITIAL RATE OF WATER ABSORPTION (kg/(m²-min))	Min 1.2 Max 4.2
ACTIVE SOLUBLE SALTS	S2
REACTION TO FIRE	Class A1

ISSUE DATE:01/02/2022

Technical data correct at time of issue. Individual dry slip weights can vary and are for guidance only. NPD = No Performance Determined. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.







AVAILABLE IN FULL, CORNER & HALF (mm)







CONTACTOS

03338 804807 upport@thebricktilecompany.com www.bricktilecompany.com