

# The Shortening Shuttle®

Economy Series

## Model #SS-611-T



Capacity: 80 Lbs / 10.5 Gal.

Min. Fryer Drain Height: 11.5 in.

Max. Dumpster Height: 49.5 in.

Overall Shipping Dims: 12 x 13 x 58 in. 27 Lbs

**Fill**

### STANDARD FEATURES:

#### Construction:

- ◆ Heavy duty construction, 0.10 thick aluminum body.
- ◆ Double walled seams and deep weld penetration.
- ◆ Perforated Baffle Screen to prevent splashing and to catch large debris.
- ◆ Poly Carbonate handle at both ends to help lessen heat transfer.

#### Works with:

- ◆ Fryers w/front, side or bottom drains.
- ◆ Fryers w/Automatic filtering systems.
- ◆ Broaster® Equipment & Pasta Cookers.
- ◆ Dumpsters up to 49.5 in. tall.
- ◆ Dumpster opening: min. of 8¼ in. x 7¾ in.
- ◆ Dumpster opening setback from front edge of dumpster: max. 3½ in.\*

#### Cautions:

- Allow shortening to cool to 120° F or less to reduce the likelihood of burns.
- Never use any of our Shortening Shuttle®s without the baffle screen in place.
- Never pour caustic cleaning products inside or on the outside of the Shortening Shuttle®.
- Always use safety gloves when using any of our Shortening Shuttle®s .

**Walk**



**Push**




**Hook**



**Squat**



**Empty**



### OPTIONS:

Stair Plate	must be ordered with a Shuttle
Wall Hook	SS-WHOOK
*Dumpster Extension	SS-611-DX
Shuttle Filter	SS-SF-100
Shuttle Cover	SS611COV
Fryer Drain Hose	FDH-??NPT
Safety Glove	Heat Resistant 914-207

**Worcester Industrial Products Corp**

7 Brookfield street Worcester, MA 01605

800-533-5711 508-757-5161 FAX 508-831-9990

sales@Shortening-Shuttle.com

www.Shortening-Shuttle.com

Specifications subject to change without notice.