



APOLLO

• **Features**

- Clean poly carbonate glasses
- UV protective
- Aptly positioned ventilation
- Flexible PVC frame
- Ergonomically design
- Comfortable elastic strap
- Impact Resistant
- Scratch Resistant

APOLLO

Material used

Temple: PC
Molding LEN/ 5 C: PC (2.2 mm thickness)
Screw: Stainless Steel

Sizes

NA

Category

II

Color

Transparent

Specifications

Weight: 52g
Frame Width: 145mm
Tip End Width: 91mm
Temple Length: 131mm



PROTECTIVE EYEWEAR – SPECTACLE

*Category: Protective
EYEWEAR – Spectacle*

*General Description:
Protection against high speed
particles at extremes of
temperature – Low energy
Impact.*



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



EYE PROTECTOR

Limits to use

The high performance poly carbonate protector is impact resistant but not unbreakable. Clean and inspect frequently. Exposure or contact with some chemical vapours or liquids may cause surface grazing and reduce impact resistance. Discard immediately when crazing. Pitting or scratches reduce vision..

Instructions for storage:

Store in its original packing in a clean dry area away from corrosive substances, solvents, without sun light. When unused, do not leave the protector out of its package or do not put it near other items such as tools or other metallic objects if they are not covered

With extremely large field of vision and outstanding fitness
Side vented
Fits over personal spectacle.
Great protection at upper and side
99% UV protection

Instruction for wearing:

To put on this protector, use both hands to pull templates apart enough or stretch the elastic strap into a comfortable position so that the protector fits perfectly.

Instructions for cleaning:

Clean under tepid water. Rinse and wipe with a soft, dry, anti-plush and non abrasive cloth. Please don't clean the lens with solvent liquid to avoid any damage from solvents

**The marking element reproduces on the oculars and on the frame are the following -
CE MALLCOM 1 FT – EN 166 FT**

Application

Use for protection while cutting, grinding or where protection from small flying particles is needed. Do not use this protector in torch welding, electrical arc welding or any other operations which produce harmful levels of infrared radiation or any kind of laser radiation.

Packaging Instruction:

25pcs/box



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in