



F667

F667

Material used

Palm – Royal blue split leather with yellow split reinforcement of 25 cm length, 12.5 cm width and 2.3-2.5 cm thick
Back – Royal blue split leather with yellow split knuckle protection
Cuff – 15 cm royal blue split leather cuff
Binding – Synthetic coloured binding tape
Liner – Cotton cloth with palm & cuff with canvas fabric

Available Size

10

Colour

royal blue

Features:

Reinforced dyed blue split welder glove with 15 cm split cuff
Provides good mechanical resistant and comfort
Total wt/ pair (g)- 365 gm
Gross wt/ carton- 13.31 kg
Chromium VI free leather according to EN 420:2003 + A1:2009

Specifications:

Liner: 190 GSM cotton cloth with palm & cuff with canvas fabric
Cuff :15 cm royal blue split leather cuff
Weight (DZP): 4380 gm



WELDER GLOVES

Royal blue split leather welder glove with yellow leather split palm reinforcement and 15 cm royal blue split cuff



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



Safe hands!!

Instruction for use

The glove should not be worn when it exist a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding. Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100°C).

Instructions for storage:

Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

Using life depends on character of activity and usage frequency.

Mallcom welder gloves provides superior comfort and dexterity with unparallel mechanical resistant properties

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

Instructions for cleaning / maintenance:

It cannot be cleaned

Do not clean in washing machine.

Put the gloves on clean and dry hands.

Check inside and out of gloves before re-use them.

Packaging Instruction:

36 pairs in a carton.



Performance according to EN 388:2003 :

4. Resistance to abrasion (from 0 to 4)

1. Resistance to cut (from 0 to 5)

3. Resistance to tear (from 0 to 4)

3. Resistance to puncture (from 0 to 4)



EN 407 :413X4X

4. Resistance to flammability (from 1 to 4)

1. Resistance to contact heat (from 1 to 4)

3. Resistance to convective heat (from 1 to 4)

X. Resistance to radiant heat (from 1 to 4)

4. Resistance to small projection from molten metal (from 1 to 4)

X. Resistance to large projection from molten metal (from 1 to 4)

Applications:

Welding operation

Hot metal handling

Hot metal sheet processing



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E: safety@mallcom.in, w : www.mallcom.in