



H044K

Features:

Dyed mustard yellow split welder glove with 15 cm split cuff

Provides good mechanical resistant and comfort

Total wt/ pair (g)- 365 gm

Gross wt/ carton- 13.231 kg

Chromium VI free leather according to EN 420:2003 + A1:2009

H044K

Material used

Palm - Yellow died split leather 25 cm length and that of 2.3-2.5 mm thick

Back - Yellow dyed split leather

Cuff - Natural split cuff

Binding - NA

Liner - Kevlar thread

Available Size

10

Color

yellow

Specifications:

Liner: Kevlar thread

Cuff : Natural split cuff

Weight (DZP): 4380 (± 10) gm



WELDER GLOVES

Dyed mustard yellow welder glove, Knitted Kevlar® and cotton platted liner, Sewn with Kevlar® thread, Natural Split leather cuff 15 cm length, Grain leather vein and knuckle protection



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



Safe hands!!

Instruction for use

The glove should not be worn when it exist a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding.

Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100°C).

Instructions for storage:

Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

Using life depends on character of activity and usage frequency

Mallcom welder gloves provides superior comfort and dexterity with unparallel mechanical resistant properties

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

Instructions for cleaning / maintenance:

It cannot be cleaned

Do not clean in washing machine.

Put the gloves on clean and dry hands.

Check inside and out of gloves before re-use them.

Packaging Instruction:

36 pairs in a carton.



Performance according to EN 388:2003 :

- 3. Resistance to abrasion (from 0 to 4)
- 2. Resistance to cut (from 0 to 5)
- 4. Resistance to tear (from 0 to 4)
- 3. Resistance to puncture (from 0 to 4)



EN 407 :413X4X

- 4. Resistance to flammability (from 1 to 4)
- 1. Resistance to contact heat (from 1 to 4)
- 3. Resistance to convective heat (from 1 to 4)
- X. Resistance to radiant heat (from 1 to 4)
- 4. Resistance to small projection from molten metal (from 1 to 4)
- X. Resistance to large projection from molten metal (from 1 to 4)

Applications:

Welding operation

Hot metal handling

Hot metal sheet processing



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E: safety@mallcom.in, w : www.mallcom.in