

H468

Features:

Yellow water repellent Velcro adjusted welder glove with Aluminium polyester inserted and wool lined Provides good mechanical resistant and comfort Total wt/pair (g)- 365 gm Gross wt/ carton- 13.31 kg Chromium VI free leather according to EN 420:2003 + A1:2009

H468

Material used

Palm – Yellow water repellent grain leather 25 cm length and that of 2.3-2.5 mm thick

Back - Yellow water repellent grain leather

Cuff – Natural split cuff with Velcro adjustment

Binding - NA

Liner – Aluminium polyester inserted and wool lined

Available Size

10

Color

yellow

Specifications:

Liner: Aluminium polyester inserted and wool lined

Stitching: 100% Kevlar®

Cuff: 20 cm natural split cuff with

Velcro adjustment

Weight (DZP): 4380 (±10) gm



WELDER GLOVES

Yellow water repellent Velcro adjusted welder glove with Aluminium polyester inserted and wool lined



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in



Safe hands!!

Instruction for use

The glove should not be worn when it exist a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding.

Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100° C).

Instructions for storage:

Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

Using life depends on character of activity and usage frequency

Mallcom welder gloves provides superior comfort and dexterity with unparallel mechanical resistant properties

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

Instructions for cleaning / maintenance:

It cannot be cleaned
Do not clean in washing machine.
Put the gloves on clean and dry hands.
Check inside and out of gloves before re-use them.

Packaging Instruction:

36 pairs in a carton.



Performance according to EN 388:2003

- 2. Resistance to abrasion (from 0 to 4)
- 1. Resistance to cut (from 0 to 5)
- 3. Resistance to tear (from 0 to 4)
- 3. Resistance to puncture (from 0 to 4)



EN 511:221

- 2. Resistance to convective heat (Levels 1-4)
- 2. Resistance to contact cold (Levels 1-4)
- 1. Water proof/permeability by water (Levels 0-1)

Applications:

Welding operation Hot metal handling Hot metal sheet processing Work in cold environment











MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City Kolkata 700091, India

 $T\colon +E: \underline{safety@mallcom.in}, w: www.mallcom.in$