



H515A

Features:

4 tips dyed red split welder glove with aluminized preox fabric back
Provides good mechanical resistant and comfort
Total wt/ pair (g)- 365 gm
Gross wt/ carton- 13.31 kg
Chromium VI free leather according to EN 420:2003 + A1:2009

H515A

Material used

Palm - Dyed red split leather of 25 cm length and that of 2.3-2.5 mm thick
Back - Reinforced with aluminized preox fabric back
Cuff - natural colored cuff
Binding - Dyed red split leather
Liner - Cotton fleece fabric

Available Size

10

Color

Red

Specifications:

Liner: cotton fleece fabric
Stitching: 100% Kevlar®
Cuff :15-20 cm cuff
Weight (DZP): 4380 (±10) gm



WELDER GLOVES

Fire and heat resistant welder glove, Aluminised Preox fabric used at back and thumb, Aluminized Preox fabric 15 cm split cuff, Sewn with Kevlar thread, Palm lined with fleecy fabric and canvas at the back of the cuff



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



Safe hands!!

Instruction for use

The glove should not be worn when it exist a risk of entanglement by moving parts of machines.

Gloves do not provide any protection against electric shock when intended to arc welding. Type A gloves are recommended for other welding processes.

There is no standardized test method at present for detecting U.V. penetration of materials for gloves.

With arc welding installations, it is not possible to protect all parts conducting the welding voltage against direct contact for operational reasons.

Can be used for working near furnaces (but the glove do not affect any protection against large splashes of molten metal), Metallurgical product handling (the glove allow the handling of hot pieces not above 100°C).

Instructions for storage:

Store the gloves in cool dry place and out of reach of sunlight in their original carton and packing.

Using life depends on character of activity and usage frequency.

Mallcom welder gloves provides superior comfort and dexterity with unparallel mechanical resistant properties

Warning

Gloves not to be worn when there is a risk of entanglement by moving parts of machines.

Instructions for cleaning / maintenance:

It cannot be cleaned
Do not clean in washing machine.
Put the gloves on clean and dry hands.
Check inside and out of gloves before re-use them.

Packaging Instruction:

36 pairs in a carton.



Performance according to EN 388:2003 :

4. Resistance to abrasion (from 0 to 4)
1. Resistance to cut (from 0 to 5)
4. Resistance to tear (from 0 to 4)
3. Resistance to puncture (from 0 to 4)



EN 407 :413X4X

4. Resistance to flammability (from 1 to 4)
1. Resistance to contact heat (from 1 to 4)
3. Resistance to convective heat (from 1 to 4)
- X. Resistance to radiant heat (from 1 to 4)
4. Resistance to small projection from molten metal (from 1 to 4)
- X. Resistance to large projection from molten metal (from 1 to 4)

Applications:

Welding operation
Hot metal handling
Hot metal sheet processing
Work in cold environment



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in