



Features:

Lightweight and durable helmet meeting a wide range of standard performance requirements.
Available with a choice of ratchet or Zip adjustment for adaptability.
Compatible with a wide range of safety products and metal-working accessories (such as Eye wear, Ear muff etc..) to provide the complete solution for your application.
Conformed for use at temperatures ranging from -10°C to +50°C.
Sturdy UV resistant HDPE Safety helmets

JASPER II

Material used

HDPE shell material
Plastic harness lining with 2 bands with 4 attachment points
Ratchet adjustment
head measurement 52 to 60 cm
Chin strap adjustment option available

Adjustable 52 - 60 cm


Sizes:

Available Colors:

White, Red, Yellow, Blue

Specifications:

Weight: 320 g (with chin strap)
No. of attachment points: 4



SAFETY HELMET

*Non Ventilated Ratchet
adjusted Industrial safety
helmet*



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in



Head Shield!!

Limits to use

The helmet life is affected by several factors, such as cold, heat, chemical products, sun light or misuse. A daily check should be performed in order to identify any sign of rendering (cracks, flaws) the helmet, its harness and accessories fragile. Any helmet having been subject to a strong shock or having wear signs should be replaced. Under normal usage conditions, this protective helmet should provide proper protection for 2 up to 3 years after the first usage, or 5 years according to the manufacturing date (written inside). If a sensitive person has an allergic reaction, remove the helmet and ask for medical advice.

Instructions for storage:

It should be stored in a dry cool place away from light, frost and in a location granting that no chemical product or sharp object bends it by falling above.

Mallcom Helmet provides superior protection to the skull and excellent durability

Instructions for cleaning:

This protective helmet may be cleaned and disinfected by means of a cloth impregnated in a low concentration cleaning solution. One shall not use any abrasive or corrosive chemical product. If this helmet cannot be cleaned by using this method, it should be replaced.

Performances:

This helmet complies with the standard IS 2925:1984



Applications:

Steel manufacturing industries
Aluminum Smelting
Foundries & Casting
Metal recycling
Refractory production
Cement manufacturing industries
Construction sites



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in