

L1102 PV

Material used

Layer 1: Polypropylene Non woven

Layer 2: Needle punched fabric

Layer 3: Melt Blown Filter media.

Layer 4: Polypropylene nonwoven

Nose Clip: Concealed aluminum nose clip

Fastening Straps – Nylon elastane blended

fastening strap

Certification Category:

FFP1

Sizes:

Universal

Available Colors:

White

Specification:

Mask: 40 GSM Polypropylene nonwoven

24 GSM Needle punch fabric

45 GSM Filter media

25 GSM Polypropylene nonwoven

Features:

Filtering half mask to protect against particles

FFP1 foldable white coloured half mask

Soft non woven fabric with nose clip for adjustment

Adjustable head loop elastic strap for fastening.

Straps: Nylon elastane blended head loop

fastening strap

Nose bar: Concealed aluminum nose clip Exhalation Valve: Rubber valve with LDPE

Plastic casing outside



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in



FACE MASK

Disposable FFP1 dust masks.
Nose bar adjustment



Safe to breathe

Limits to use

Use the mask in well ventilated areas. Mask must be positioned correctly in order to provide the expected level of protection. Do not use if facial hair (Beard or Sideburns) prevent the mask from being fully sealed, and leakage is detected. Leave the area immediately if you experience breathing problems and/or dizziness or faintness. Do not make any modifications to the mask, and discard it if there is any damage to it. Failure to observe these instructions for use may have adverse effects on the health of the user and expose him to serious or even life threatening risks. This dust mask shall not be used for than one shift. If a sensitive person has an allergic reaction, remove the mask and ask for medical advice.

Instructions for storage:

Store in its original packaging away from humidity under normal temperature in a cool, dark place.

Mallcom face mask provides ultimate protection to the face keeping away all mere kind of harmful chemicals, industrial hazards from it with superior comfort and durability

Instructions for cleaning:

This mask is meant for single usage only.

Packaging:

10 pieces are available in one primary box each carton contains 20 primary boxes.

Applications:

Meant for usage in industrial sector, Cleaning purposes etc



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in

Performance:

Dust and aerosol filters	
Type	P1
Code	White
Protection	Protects from coarse solid particles without specify toxicity (Calcium Carbonate)
Filter efficiency	
<4 AVE 80% FF P1	

EU –Type Examination under PPE REGULATION 2016/425 with EN 149:2001 + A1:2009 standard done by: SGS Fimko OY Takomotie 8 Helsinki, 00380 Finland Notified Body No: 0598

This face mask complies with BIS 9473:2002. This declaration is identical to the Personal Protective Equipment with BIS attestation:

ATTACHMENT TO LICENSE NO. CM/L-5100189295

Marking:

Filtering half mask: Name of the manufacturer identification:
MALLCOM, Product name:
L1102PV and class symbol:
FFP1 NR, number and year of the standard EN 149:2009
+A1:2009, pictogram