



M1202PV FFP2 NR

Features:

Filtering half mask to protect against particles
FFP2 foldable white coloured half mask
Soft non woven fabric with nose clip for adjustment
Adjustable head loop elastic strap for fastening.

M1202 PV

Material used

Layer 1: Polypropylene Non woven
Layer 2: Needle punched fabric
Layer 3: Melt Blown Filter media.
Layer 4: Melt Blown Filter media.
Layer 5: Polypropylene nonwoven
Nose Clip: aluminum nose clip
Fastening Straps – Nylon elastane blended fastening strap

Certification Category:

FFP2

Sizes:

Universal

Available Colors:

White

Specification:

Mask: 40 GSM Polypropylene nonwoven
45 GSM Needle punch fabric
30 GSM Filter media
25 GSM Filter media
25 GSM Polypropylene nonwoven

Straps: Nylon elastane blended Head-loop fastening strap
Nose bar: aluminum nose clip
Exhalation valve: Rubber valve with LDPE plastic casing outside



FACE MASK



*Disposable FFP2 dust masks.
Nose bar adjustment*



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
Kolkata 700091, India

T: +E : safety@mallcom.in, w : www.mallcom.in



Safe to breathe

Limits to use

Use the mask in well ventilated areas. Mask must be positioned correctly in order to provide the expected level of protection. Do not use if facial hair (Beard or Sideburns) prevent the mask from being fully sealed, and leakage is detected. Leave the area immediately if you experience breathing problems and/or dizziness or faintness. Do not make any modifications to the mask, and discard it if there is any damage to it. Failure to observe these instructions for use may have adverse effects on the health of the user and expose him to serious or even life threatening risks. This dust mask shall not be used for than one shift.If a sensitive person has an allergic reaction, remove the mask and ask for medical advice.

Instructions for storage:

Store in its original packaging away from humidity under normal temperature in a cool, dark place.

Our superior quality face mask provides excellent protection from very fine dust particles, fumes, oil & aqueous based mist

Instructions for cleaning:

This mask is meant for single usage only.

Packaging:

10 pcs - 10 pieces are available in one box
 50 pcs - 50 pcs in one plastic poly bag
 500 pcs - 50 pcs in one plastic poly bag, 10 poly bags in a carton

Applications:

Meant for usage in industrial sector, Cleaning purposes etc



MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City
 Kolkata 700091, India

T: +E: safety@mallcom.in, w: www.mallcom.in

Performance:

Dust and aerosol filters	
Type	P2
Code	Yellow
Protection	Protects from solid and or/ liquid aerosol warned to be hazardous or irritating (Silica, Sodium)
Filter efficiency	

EU -Type Examination under PPE REGULATION 2016/425 with EN 149:2001 + A1:2009 standard done by: SGS Fimko OY Takomotie 8 Helsinki, 00380 Finland Notified Body No: 0598

This face mask complies with BIS 9473:2002. This declaration is identical to the Personal Protective Equipment with BIS attestation:

ATTACHMENT TO LICENSE NO. CM/L-5100189295

Marking:

Filtering half mask: Name of the manufacturer identification: Mallcom, Product name: M1202 PV and class symbol: FFP2 NR, number and year of the standard EN 149:2009 +A1:2009, pictogram