



*PLUTO*

### Features

With extremely large field of vision  
and outstanding fitness  
Side covered  
Fits over personal spectacle.  
Great protection at upper and side  
99% UV protection

## PLUTO

### Material used

Temple Front: Nylon  
Temple Tube: Nylon  
Temple Tips: Nylon  
Vibvets: PC  
Screw: 2.5\*1.6\*8.0 Stainless Steel  
Lens 4C: PC

### Sizes

NA

### Category

II

### Color

Temple: Transparent  
Back guard: Black

### Specifications

Weight: 32g ± 2g  
Frame Width: 140 ± 2mm  
Distance between both Tips: 85 ± 2  
Temple Length: 107-117mm



## PROTECTIVE EYEWEAR – SPECTACLE

*Category: Protective  
EYEWEAR – Spectacle*

*General Description:  
Protection against high speed  
particle – Low energy Impact.*



### MALLCOM INDIA LTD

EN 12, Sector V, Salt Lake City  
Kolkata 700091, India

T: +E : [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)



## EYE PROTECTOR

### Limits to use

The high performance poly carbonate protector is impact resistant but not unbreakable. Clean and inspect frequently. Exposure or contact with some chemical vapours or liquids may cause surface grazing and reduce impact resistance. Discard immediately when crazing. Pitting or scratches reduce vision..

### Instructions for storage:

Store in its original packing in a clean dry area away from corrosive substances, solvents, without sun light. When unused, do not leave the protector out of its package or do not put it near other items such as tools or other metallic objects if they are not covered

---

*With extremely large field of vision and outstanding fitness*

*Side covered*

*Fits over personal spectacle.*

*Great protection at upper and side*

*99% UV protection*

---

### Instruction for wearing:

To put on this protector, use both hands to pull templates apart enough or stretch the elastic strap into a comfortable position so that the protector fits perfectly.

### Instructions for cleaning:

Clean under tepid water. Rinse and wipe with a soft, dry, anti-plush and non abrasive cloth. Please don't clean the lens with solvent liquid to avoid any damage from solvents

**The marking element reproduces on the oculars and on the frame are the following -  
CE TIGER 1 F – EN 166 F**

### Application

Use for protection while cutting, grinding or where protection from small flying particles is needed. Do not use this protector in torch welding, electrical arc welding or any other operations which produce harmful levels of infrared radiation or any kind of laser radiation.

### Packaging Instruction :

25pcs/box



**MALLCOM INDIA LTD**

EN 12, Sector V, Salt Lake City

Kolkata 700091, India

T: +E: [safety@mallcom.in](mailto:safety@mallcom.in), w : [www.mallcom.in](http://www.mallcom.in)