# VT-60012 12W BACKLIT SURFACE MOUNTED PANEL 6500K SQ

## TECHNICAL INFORMATION

| | |
|---|---|
| **Dimmable:** | No |
| **Model:** | VT-60012-SQ |
| **On/Off Cycles:** | >15000 |
| **Input Current:** | 71mA |
| **CRI:** | >80 |
| **Color Temperature:** | 6500K |
| **Watts:** | 12 |
| **Lumens:** | 1200 |
| **Input Power:** | AC:220-240V, 50/60Hz |
| **Unit Color:** | White |
| **Color for Web:** | White |
| **Dimension:** | 167.3x167.3x30.7mm |
| **Operation Temperature:** | -20°C to +45°C |
| **LED Chip Type:** | SMD |
| **Energy Rating Label:** | F (2021) |
| **Energy Saving:** | 85 Energy |
| **Long Life:** | 20,000 Hours |
| **IP Rating:** | IP20 |

## FEATURES

- Strong and sturdy body Backlit Mini Panels
- High quality power driver ensures reliable lifetime
- Designed with high efficiency LED SMD chips.
- No Lead or Mercury content hence Environment friendly
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.

A↑G F
energy-rating-icon-F

IP20 STANDARD

02 YEAR WARRANTY

## LISTING DETAILS

| | |
|---|---|
| **SKU:** | 10497 |
| **Model:** | VT-60012-SQ |
| **EAN:** | 3800170208841 |
| **Commodity Code:** | 94051140 |

## PACKAGING

| | |
|---|---|
| **Gross Weight (Kgs):** | 0.23 |
| **Unit CBM:** | 0.0013 |
| **Dimension:** | 167.3x167.3x30.7mm |

## MASTER BOX PACKAGING

| | |
|---|---|
| **Box Qty:** | 60 |
| **Qty Per Pallet:** | 1200 |
| **Length (Box) mm:** | 175 |
| **Width (Box) mm:** | 35 |
| **Height (Box) mm:** | 175 |