



VT-60024 24W BACKLIT SURFACE MOUNTED PANEL 3000K SQ



TECHNICAL INFORMATION

Dimmable:	No
Model:	VT-60024-SQ
On/Off Cycles:	>15000
Input Current:	160mA
CRI:	>80
Color Temperature:	3000K
Watts:	24
Lumens:	2500
Input Power:	AC:220-240V, 50/60Hz
Unit Color:	White
Color for Web:	Warm White
Body Type:	Plastic
Dimension:	287x287x30.7mm
Operation Temperature:	-20°C to +45°C
LED Chip Type:	SMD
Energy Rating Label:	F (2021)
Energy Saving:	85 Energy
Long Life:	20,000 Hours
IP Rating:	IP20
Product Information Document (EU Fiche):	https://files.plytix.com/api/v1.1/file/public_files/pim/assets/df/a1
Energy Label EU :	https://files.plytix.com/api/v1.1/file/public_files/pim/assets/df/a1

IP20 | **02**
STANDARD | WARRANTY

FEATURES

- Strong and sturdy Plastic body Backlit Mini Panels
- High quality power driver ensures reliable lifetime
- Designed with high efficiency LED SMD chips.
- No Lead or Mercury content hence Environment friendly
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.

LISTING DETAILS

SKU:	10514
Model:	VT-60024-SQ
EAN:	3800170208889
Commodity Code:	

PACKAGING

Gross Weight (Kgs):	0.56
Unit CBM:	0.00372
Dimension:	287x287x30.7mm

MASTER BOX PACKAGING

Box Qty:	20
Qty Per Pallet:	
Length (Box) mm:	300
Width (Box) mm:	35
Height (Box) mm:	300