





TECHNICAL INFORMATION

| Input Power: | DC:24V |
|------------------------|----------------|
| Long Life: | 20,000 Hours |
| LED Chip Type: | SMD |
| CRI: | >80 |
| Operation Temperature: | -20°C to +45°C |
| Dimmable: | No |
| Beam Angle: | 120° |
| Color Temperature: | 4000K |
| Dimension: | 10mm |
| Watts per meter: | 18 |
| lumens per watt: | 135 |
| Lumens per meter: | 2430 |
| Current per meter: | 0.75A |
| Roll Qty: | 5M |













FEATURES

- Stable SMD technology for better reliability and longer lifespan
- Low Voltage flexible ribbon available in DC:24V
- 5M Roll quantity
- Flexible installation: Cutting and reconnect the strip as you wish to suit your application
- $^{\bullet}\,$ Suitable for illuminating borders, edges, cabinets, bars and areas with limited space for installation

STRIPLIGHTS 2835 238 | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 212600 -

View more details



PACKAGING

Gross Weight (Kgs): 0.04 Unit CBM: 0.000185 Dimension: 10mm

MASTER BOX PACKAGING

Box Qty: 400 Length (Box) mm: 10 Width (Box) mm: 210 Height (Box) mm: 260

LISTING DETAILS

Commodity Code: 9405403990 Ean Code: 3800157676175