



TECHNICAL INFORMATION

Watts:	5
Lumens:	700
Shape:	Square
Input Power:	AC:220-240V, 50Hz
Long Life:	20,000 Hours
Unit Color:	Black
Body Type:	Aluminium
LED Chip Type:	SMD
CRI:	>80
Operation Temperature:	-25°C to +50°C
Dimmable:	No
Beam Angle:	120°
Color Temperature:	4000K
Dimension:	100x100x100mm
lumens per watt:	140

SQUARE BRIDGELUX | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions.

SKU: 217087 - 1263 938

[View more details](#)



FEATURES

- Modern range of Up-Down lights with sleek and stylish designs
- Elegant replacement for traditional up-down lighting
- Fitted with high quality SMD chips for better reliability and longer lifespan
- Robust Aluminium build for efficient heat dissipation
- Suitable for living rooms, pathways, balconies, facades etc.

PACKAGING

Gross Weight (Kgs): 0.69
Unit CBM: 0.001573
Dimension: 100x100x100mm

MASTER BOX PACKAGING

Box Qty: 20
Length (Box) mm: 110
Width (Box) mm: 110
Height (Box) mm: 110

LISTING DETAILS

Commodity Code: 9405409990
Ean Code: 3800157678599