



### TECHNICAL INFORMATION

Input Power:	DC:24V
Long Life:	20,000 Hours
Body Type:	PVC
LED Chip Type:	SMD
CRI:	>80
Dimmable:	No
Beam Angle:	120°
Color:	4000K
Dimension:	10mm
Input Current:	0.375A
Watts per meter:	9
Lumens per meter:	500
Current per meter:	0.375A
No. Of Led:	60
Roll Qty:	5M

### STRIPLIGHTS 5050 60 IP65 | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 2563 - 2938

[View more details](#)

### SMD 5050 60 LED'S



80%  
ENERGY  
SAVING



120°  
Beaming Angle



### FEATURES

- Stable SMD technology for better reliability and longer lifespan
- Built with DC Female plug for easy installation
- 5M Roll quantity
- Low Voltage flexible ribbon available in DC:24V
- Flexible installation: Cutting and reconnect the strip as you wish to suit your application
- Suitable for indoor and outdoor applications

CE/EMC



### PACKAGING

Gross Weight (Kgs): 0.1227  
Unit CBM: 0.003645  
Dimension: 10mm

### MASTER BOX PACKAGING

Box Qty: 100  
Qty Per Pallet: 3600  
Length (Box) mm: 50  
Width (Box) mm: 270  
Height (Box) mm: 270

### LISTING DETAILS

Commodity Code: 9405403990  
EanCode: 3800157637541