



TECHNICAL INFORMATION

Watts:	1.5
Lumens:	120-150
Input Power:	DC:12V
Long Life:	20,000 Hours
Body Type:	ABS + Aluminium Plate
LED Chip Type:	SMD
CRI:	>75
Operation Temperature:	-25°C to +50°C
Dimmable:	No
Beam Angle:	120°
Color:	3000K
Dimension:	87x15x10mm

MODULES 2835 3 IP67

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 5124 - 1541 2938

[View more details](#)

2835 3 SMD MODULE



IP67
RATING

EASY TO INSTALL
& Low maintenance

120°
Beaming Angle

DC : 12V



FEATURES

- Reliable high quality super bright SMD SMD LED Module for Signage industry
- IP67 rated waterproof modules: Suitable for mounting near water surfaces
- Super bright output: 120-150 lumens per module
- Suitable for boat cabin and deck lighting, stair lighting, sign advertising, gardens and exterior lighting
- Recommended daily usage: 10 - 12 hours *Exceeding recommended daily usage will void warranty

CE/EMC CE/LVD



PACKAGING

Gross Weight (Kgs): 0.014
Unit CBM: 0.0000153
Dimension: 87x15x10mm

MASTER BOX PACKAGING

Box Qty: 2000
Length (Box) mm: 85
Width (Box) mm: 10
Height (Box) mm: 18

LISTING DETAILS

Commodity Code: 9405403990
EanCode: 3800157621687