



### TECHNICAL INFORMATION

Watts:	20
Lumens:	1400
Input Power:	AC:220-240V, 50Hz
Long Life:	30,000 Hours
Unit Color:	White
Body Type:	Aluminium
PF:	>0.5
LED Chip Type:	SMD
CRI:	>80
Operation Temperature:	-20°C to +45°C
Dimmable:	Yes
Beam Angle:	100°
Color:	RGB+W/WW/DW
Dimension:	141.6x42.7x126.3mm

### COLOR CHANGING FLOODLIGHT

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 5984 - 931 940

[View more details](#)

### SMART FLOODLIGHT

**Step.1**  
Install the floodlight, Download V-TAC Smart App & Register an account with QR

**Step.2**  
Pair with V-TAC Smart App

**Step.3**  
Enjoy single device or Group/family function operations

SHARE THE NETWORK WITH GROUP OR FAMILY VIA QR CODE



### FEATURES

- Wirelessly control Floodlight with V-TAC Smart App
- Switch lights off, change colours, dim the lights, group light and more using the V-TAC Smart App
- Strong and durable aluminium body
- IP65 weather-resistant rating
- Easy to install and pair the light with the App
- Suitable for gardens, patio, building etc.

CE/EMC

CE/LVD



### PACKAGING

Gross Weight (Kgs): 0.516  
Unit CBM: 0.000975  
Dimension: 141.6x42.7x126.3mm

### MASTER BOX PACKAGING

Box Qty: 20  
Qty Per Pallet: 800  
Length (Box) mm: 130  
Width (Box) mm: 150  
Height (Box) mm: 50

### LISTING DETAILS

Commodity Code: 9405403990  
EanCode: 3800157640411