



TECHNICAL INFORMATION

Watts:	29
Input Power:	AC:200-240V, 50/60Hz
Body Type:	ABS Plastic
Operation Temperature:	-25°C to +50°C
Dimmable:	No
Dimension:	142x43.5x31mm
Output Voltage:	DC:26-36V
Input Current:	0.16A
Output Current:	800mA

DRIVER - FLICKER FREE

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 6271 - 1563 2938

[View more details](#)



FEATURES

- 29 watts flicker free driver
- EMC, SELV and LVD Compliant
- High quality capacitors for better case temperature
- Compatible with V-TAC LED Panels

CE/EMC

CE/LVD



PACKAGING

Gross Weight (Kgs): 0.15
 Unit CBM: 0.00384
 Dimension: 142x43.5x31mm

MASTER BOX PACKAGING

Box Qty: 50
 Qty Per Pallet: 400
 Length (Box) mm: 35
 Width (Box) mm: 60
 Height (Box) mm: 160

LISTING DETAILS

Commodity Code: 8504409090
 EanCode: 3800157614443