

Product Spec Sheet



VT-49104 100W SMD FLOODLIGHT F-CLASS 4000K BLACK BODY



FEATURES

- High quality LED SMD chip and high power driver
- Comparing with traditional halogen floodlights it can save upto 80% Energy
- Constant current Integrated IC driver Built in driver no external power supply required
- Built Strong and durable with Aluminium Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.

TECHNICAL INFORMATION

Dimmable:	No
Instant Start:	0-100% in < 1s
CRI:	>70
On/Off Cycles:	>15000
Model:	VT-49104-B
Beam Angle:	110°
Color Temperature:	4000K
Watts:	100
Lumens:	8700
Input Power:	AC:220-240V, 50/60Hz
Unit Color:	Black
Color for Web:	Day White
Body Type:	Aluminium
Dimension:	270x27x222mm
Operation Temperature:	-20°C to +40°C
PF:	>0.9
LED Chip Type:	SMD
Energy Rating Label:	F (2021)
Energy Saving:	80 Energy
Long Life:	25,000 Hours
IP Rating:	IP65

IP65 STANDARD



LISTING DETAILS

SKU:	6722
Model:	VT-49104-B
EAN:	3800157684330
Commodity Code:	94054210

PACKAGING

Gross Weight (Kgs):	1.26 0.002425	
Unit CBM:		
Dimension:	270x27x222mm	

MASTER BOX PACKAGING

Box Qty:	10	
Qty Per Pallet:	500	
Length (Box) mm:		
Width (Box) mm:		
Height (Box) mm:		