



### TECHNICAL INFORMATION

Watts:	2
Lumens:	280
Long Life:	20,000 Hours
Unit Color:	Grey
Body Type:	PC + AL
LED Chip Type:	SMD-Samsung Chip
CRI:	>80
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	120°
Color:	3000K
Dimension:	140x140x500mm
Detection Range:	3-5m
Battery Type:	Lithium 3.7V/2600mAh
Charging Time:	4-6 Hours
Working Time:	3-12 Hours

### SOLAR BOLLARD LIGHTS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 785 - 1271 939

[View more details](#)

### SPECIAL FEATURES



### FEATURES

- Solar Light built with highly efficient Samsung chips.
- Designed with sensor, offering 2 operation modes.
- Sensor Mode - Automatically turns on at dusk to 10% light & when motion detected turns 100% light On. Turns to 10% light when no motion detected & turns Off at dawn.
- Constant Brightness Mode - Automatically turns on at dusk to 100% light and works constantly till the battery capacity is reduced to zero.
- Solar powered zero electricity cost
- Easy to install(cordless) & low maintenance
- Suitable for Pathways, Garden, Patio and similar outdoor environment

### PACKAGING

Gross Weight (Kgs): 1.698  
Unit CBM: 0.011475  
Dimension: 140x140x500mm

### MASTER BOX PACKAGING

Box Qty: 10  
Qty Per Pallet: 120  
Length (Box) mm: 150  
Width (Box) mm: 150  
Height (Box) mm: 510

### LISTING DETAILS

Commodity Code: 9405403990  
EanCode: 3800157643771

CE/EMC

CE/LVD

