





TECHNICAL INFORMATION

Lumens:	4200	
Input Power:	DC:10V	
Long Life:	20,000 Hours	
Unit Color:	Black	
Body Type:	Aluminium	
LED Chip Type:	SMD	
CRI:	>70	
Operation Temperature:	-20°C to +45°C	
Dimmable:	No	
Beam Angle:	120°	
Color:	4000K	
Dimension:	437x90x356mm	
Battery Type:	25000mAh	
Charging Time:	4 Hours	
Working Time:	8 Hours	
Solar Panel:	50W	





FEATURES

- Solar Powered Floodlight Zero electricity cost.
- $^{\bullet}\,$ Designed with Remote control, Auto and timer function.
- $^{\bullet}\,$ Flexible installation, designed with solar panel with 5 meter wire length
- Perfectly built for outdoor with Ingress protection of IP65
- Suitable for Pathways, Garden, Patio and similar outdoor environment

C€/EMC

C€/LVD





SOLAR FLOODLIGHTS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 8578 - 938 View more details



PACKAGING

Gross Weight (Kgs): 7.485
Unit CBM: 0.03672
Dimension: 437x90x356mm

MASTER BOX PACKAGING

Box Qty: 2
Qty Per Pallet: 80
Length (Box) mm: 120
Width (Box) mm: 450
Height (Box) mm: 680

LISTING DETAILS

Commodity Code: 9405403990 EanCode: 3800157645638