



### TECHNICAL INFORMATION

Lumens:	3000
Unit Color:	Grey
LED Chip Type:	SMD-Samsung Chip
CRI:	>80
Operation Temperature:	-20°C to +45°C
Beam Angle:	120°
Color Temperature:	4000K
Dimension:	320x100x720mm
Battery Type:	LifePO4 6.4V Battery
Charging Time:	4-6 Hours Sunlight Charging
Working Time:	8-10 Hours
No. Of Led:	572
Wire Length:	1.2m

### SOLAR STREETLIGHTS PRO | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

### FEATURES

- Solar Powered streetlight - Zero electricity cost
- Designed with remote control and timer function
- Maximum Installation and Mounting Height 6-8 Meters
- Perfectly built for outdoor application with Ingress protection of IP65
- Includes Protruding Pole, Mounting Arm, Solar Panel, 1.2M Cable, Expansion Screws, Solar Panel Bracket, 1 Expansion Plate and Remote Control
- Suitable for Pathways, Garden, Patio and similar outdoor environment



### LISTING DETAILS

Ean Code: 3800170200630

### PACKAGING

Gross Weight (Kgs):	14
Unit CBM:	0.090299
Dimension:	320x100x720mm

### MASTER BOX PACKAGING

Box Qty: 1