

## TECHNICAL SPECIFICATIONS

|                      |                                                                             |                            |                         |
|----------------------|-----------------------------------------------------------------------------|----------------------------|-------------------------|
| Collection:          | Moduleo 55 Woods                                                            | Wear Layer:                | 0.55mm                  |
| Country of Origin:   | Belgium                                                                     | Units Per Box:             | 14                      |
| Colours:             | 1 Standard                                                                  | m <sup>2</sup> per box:    | 3.62                    |
| Product Thickness:   | 2.50mm                                                                      | m <sup>2</sup> per pallet: | 202.72                  |
| Hard Flooring Size:  | 196mm x 1320mm                                                              | Finish:                    | Matte                   |
| Installation Method: | Direct Stick                                                                | Surface:                   | Saw Cut Emboss (EMB 28) |
| Notes:               | Available for longer lead, specification projects - 16 week turnaround time | Profile:                   | Micro Bevel             |
| Type:                | Vinyl Plank                                                                 | Protective Coating:        | Protectonite®           |

## PERFORMANCE

|                        |                                                                                                          |
|------------------------|----------------------------------------------------------------------------------------------------------|
| Flammability:          | (EN ISO 9239) CRF 6.4kW/m2 #                                                                             |
| Colourfast to light:   | (EN ISO 105-B02) ≥6                                                                                      |
| Light Reflectance:     | Available on Request                                                                                     |
| Classification:        | (EN ISO 10874) 23, 33, 42                                                                                |
| Smoke Value:           | (EN ISO 9239) 130% minutes                                                                               |
| Dimensional Stability: | (EN ISO 23999) ≤0.05%                                                                                    |
| Abrasion Rating:       | (EN 660-2) Group T                                                                                       |
| Residual Indentation:  | (EN ISO 24343-1) Norm: ≤0.10mm, 0.03mm                                                                   |
| Castor Chair:          | (EN ISO 4918) No Damage                                                                                  |
| Slip Resistance:       | (AS 4586) P2, R9                                                                                         |
| Recommended Adhesive:  | Refer to our GH Commercial Adhesive Guide <a href="http://www.ghcommercial.com">www.ghcommercial.com</a> |

## SUSTAINABILITY

|                       |                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Indoor Air Quality:   | Green Building Council Compliant for VOC emission rate limits                                                                                  |
| Product Transparency: | Global Green Tag, GreenRate Level A certified                                                                                                  |
| Accreditation:        | Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body. |



# Fazino Maple



0780

28920

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial vinyl plank floors must be installed in accordance with the relevant Australian Standards and in conjunction with GH Commercial Vinyl Plank Floors Installation Instructions.

\* This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitation of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from [www.moduleo.com.au](http://www.moduleo.com.au). †Terms and conditions apply to all commercial warranties - contact your local GH Commercial Account Manager.