restD



TECHNICAL SPECIFICATIONS

Collection:	Relaxing Floors
Country of Origin:	Australia
Colours:	8 Standard
Yarn:	Duracolor® Tricor Solution Dyed Nylon
Surface Texture:	Textured Multi Coloured Loop Pile
Gauge:	47/10cm (1/12th Gauge)
Product Thickness:	7.50mm
Pile Weight:	746g/m²

Backing:	Enviro Bac®
Carpet Tiles & Planks Size:	304.8mm x 914.4mm
Installation Method:	Monolithic, Monolithic Stepping, Half- Lap, Plank, Half-Lap, Brick Ashlar, Random, Herringbone, Basket Weave
Туре:	Carpet Tiles and Planks
Units Per Box:	16
m² per box:	4.459
m² per pallet:	120.39
Pattern Repeat:	Not Applicable

PERFORMANCE

Anti-Static: (AATCC 134) <3.5KV at 21°C & 20% Relative Humidity

Flammability: Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for

flooring in Class 2-9 buildings~

Light Reflectance: Available on Request

Stain Resistance: Duracolor® Tricor - Permanent, Built into fibre

ACCS Rating: Contract Extra Heavy Duty - 4 Star
Contract Guarantee: 15 Years Available on Request*

Recommended Adhesive: Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

Soil Resistance: EcoSentry Soil Treatment

SUSTAINABILITY

PVC Minimisation: PVC Free

Indoor Air Quality: Green Building Council Compliant for VOC emission rate limits

Product Transparency: Declare Red List Free

Recycled Content: Duracolor® Tricor yarn contains 34% pre-consumer recycled content.

Green Star: Environmental Certification Scheme (ECS) Level 4 Maximum Points

Accreditation: Manufactured under a quality, environmental and health and safety system certified

and complying with ISO 9001, ISO 14001 and AS 4801 by accredited certification

bodies.

















restD










0961 HARMONY



0969 SOLITUDE



0967 PAUSE



0922 SANCTUARY



0965 BLUE BLISS



0949 EASY BREEZY



0829 FOCUS

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpet tiles and planks must be installed in accordance with AS2455 Parts 1 & 2 (latest version) and the GH Commercial Carpet Tile/Plank Installation Instructions.

Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.

 $\sim\!\!$ Test results and certificates are available on request.

*Guarantee is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.