



Premium Quality Safes You Can Trust







Safes for Every Application – Commercial • Residential • Small Businesses



The Finest Fire and Burglary Protection Available Anywhere in the World!

Gardall designs and manufactures fire and burglary resistive safes to meet or exceed many different standards and specifications.

Standard Safe Classifications

To understand how our safes are classified, here is a brief explanation of the labels you'll find on them.

Fire Protection – Two-Hour 1850° or One-Hour 1700°

Gardall fire-resistive safes meet or exceed Underwriters' Laboratories specifications for explosion, fire endurance and drop tests.

Two-Hour exposure to severe fire with an exterior temperature to 1850°F, and an interior temperature that does



not exceed 350°F (paper chars at 405°F) for two hours and cool down.

One-Hour exposure to severe fire with an exterior temperature to 1700°F, and an interior temperature that does



not exceed 350°F (paper chars at 405°F) for one hour and cool down.

Residential Security Container Burglary Label

Gardall's 2-Hour Burglary Fire, BF and FB models have passed the U.L.-



R.S.C. label test for burglary protection.

Burglary Protection

Gardall safes with the Class "B" or Class "C" Burglary Insurance Rating allow you to receive insurance coverage in accordance with the Broad Form and Mercantile Safe Insurance classifications. Pertinent insurance information is available from Insurance Service Office, 160 Water Street, New York, NY 10038.

Gardall safes can be supplied with an Underwriters' Laboratory Group II combination lock, U.L. listed key-op lock, U.L. listed dual key lock or a U.L. listed push button electronic lock.

Gardall Lifetime Replacement Warranty

Gardall Safe Corporation assures to the original end consumer, replacement – free of charge – of any Gardall Fire-Resistive Record Safe damaged beyond repair by fire with a then-current production model of a comparable value. This warranty is exclusive and in lieu of any warranty of merchantability, fitness for particular purpose or other warranties of qualities, whether expressed or implied, and of all other liabilities and obligations on the manufacturer's part.

Gardall Safe Corporation reserves the right to inspect any record safe prior to replacement. Copies of insurance reports or documents pertaining to fire loss will be furnished to Gardall Safe Corporation upon request.

Gardall Safe Corporation specifically assumes no liability for installation or other charges incurred by the owner in connection with the replacement of any record safe and assumes no liability for damage to contents or personal property contained in any such file or any consequential damages of any nature or description.



Commercial Light Duty Cash Management Safes

If you need to store register trays or if you have a problem with pilferage/cash disappearances, our cash management safes may be the answer.

LCF2820 and LCF3214 have locked depositories and a separate location for manager's change supply.

	Outside Dimensions				Inside Dimensions			Door	Weight
Model	Н	W	D		Н	W	D	Size	(lbs.)
LCF3020	30"	20"	20"		19½"	19½"	17"	20"x17"	201
LCF2820	28"	20"	16"	Тор	8"	16"	13"	8%"×16¾"	174
				Bottom	8½"	16"	13"		
LCF3214	32"	14"	14"	Тор	11"	13"	11"	10½"×11"	136
				Bottom	12"	13"	11"		

Commercial Light Duty Depository/ Undercounter Safes

When price is the objective, these safes may be your solution. With a 1/2" plate steel door and a formed



door jam, these safes will resist most sledgehammer attacks. Safes have four anchor holes and an independent relocker for increased burglary protection.

	Outside Dimensions			Insid	de Dimens	ions	Door	Weight
Model	Н	W	D	Н	W	D	Size	(lbs.)
LC1414	14"	14"	14"	13½"	13½"	11"	10½"x10¾"	68
LCS1414	14"	14"	14"	13"	13"	11"	10½"×10¾"	68
LCF2014*	20"	14"	14"	10"	13"	11"	10½"x11"	84
LCR2014*	20"	14"	14"	11"	13"	11"	10½"x11"	89

UL listed, S&G Group II combination lock

* Also available with dual key lock



Manufacturing Premium Quality Safes Since 1950















