



### **Premium Quality Safes You Can Trust**







Safes for Every Application – Commercial • Residential • Small Businesses



# The Finest Fire and Burglary Protection Available Anywhere in the World!

Gardall designs and manufactures fire and burglary resistive safes to meet or exceed many different standards and specifications.

#### Standard Safe Classifications

To understand how our safes are classified, here is a brief explanation of the labels you'll find on them.

## Fire Protection – Two-Hour 1850° or One-Hour 1700°

Gardall fire-resistive safes meet or exceed Underwriters' Laboratories specifications for explosion, fire endurance and drop tests.

Two-Hour exposure to severe fire with an exterior temperature to 1850°F, and an interior temperature that does



not exceed 350°F (paper chars at 405°F) for two hours and cool down.

One-Hour exposure to severe fire with an exterior temperature to 1700°F, and an interior temperature that does



not exceed 350°F (paper chars at 405°F) for one hour and cool down.

#### Residential Security Container Burglary Label

Gardall's 2-Hour Burglary Fire, BF and FB models have passed the U.L.-



R.S.C. label test for burglary protection.

#### **Burglary Protection**

Gardall safes with the Class "B" or Class "C" Burglary Insurance Rating allow you to receive insurance coverage in accordance with the Broad Form and Mercantile Safe Insurance classifications. Pertinent insurance information is available from Insurance Service Office, 160 Water Street, New York, NY 10038.

Gardall safes can be supplied with an Underwriters' Laboratory Group II combination lock, U.L. listed key-op lock, U.L. listed dual key lock or a U.L. listed push button electronic lock.

#### Gardall Lifetime Replacement Warranty

Gardall Safe Corporation assures to the original end consumer, replacement – free of charge – of any Gardall Fire-Resistive Record Safe damaged beyond repair by fire with a then-current production model of a comparable value. This warranty is exclusive and in lieu of any warranty of merchantability, fitness for particular purpose or other warranties of qualities, whether expressed or implied, and of all other liabilities and obligations on the manufacturer's part.

Gardall Safe Corporation reserves the right to inspect any record safe prior to replacement. Copies of insurance reports or documents pertaining to fire loss will be furnished to Gardall Safe Corporation upon request.

Gardall Safe Corporation specifically assumes no liability for installation or other charges incurred by the owner in connection with the replacement of any record safe and assumes no liability for damage to contents or personal property contained in any such file or any consequential damages of any nature or description.





#### **Economical Two-Hour Record Safes**

Gardall offers a full range of two-hour record safes, for residential or commercial use. All models are available with an attractive two-tone glossy finish. All models carry a SP120 Two-Hour Fire Label.

 Gardall Lifetime Replacement Warranty (see inside front cover)

#### Standard Features (Models 1913-4422)

- UL listed, S&G Group II combination lock
- 3 way bolt work (5 active bolts, Models 3918/4422)
- Day lock
- Pull out inner key locking compartment
- Center bolt down hole with hardware included
- SP120 Fire Test Extreme furnace temperature up to 1850°F for two hours. The interior of the safe was not damaged and only rose to 302°F for a high temperature

Model	Outside Dimensions H W D			Inside Dimensions H W D			Approx. Weight (lbs.)	Shelves
Model		• • •			• • • • • • • • • • • • • • • • • • • •		TTCIGITE (185.)	51101705
SS1913-G-CK▲	24¾"	19¾"	18¼"	15¼"	12½"	11¾"	210	1
SS2517-G-CK▲	31"	23"	20"	21½"	16½"	13¼"	352	1
SS3918-G-CK▲	46"	251/4"	25"	35"	18¼"	17¾"	650	2
SS4422-G-CK▲	50¾"	291/4"	25¼"	39½"	22½"	17¾"	725	2

▲ S&G mechanical lock standard Add 1½" to outside depth for dial and handle.



Manufacturing Premium Quality Safes Since 1950















