INTERNATIONAL EUROVAULT EVRH

Superior Depository Storage for Daily Cash Management

• Activated Depository Slot

Inside compartment provides temporary storage for excess cash throughout the day

• High Security Construction

Using high density aggregate compound

• Inside Key Lock -

Dual nose high security key lock on inside compartment

Auto firing passive relocker

Protects locks during forced entry attempt

3-Way Boltwork

Massive 1½" chrome-plated bolts with auto-lock bolt detent keeps bolts extended when door is closed & retracted when door is open

Door and Body

2" thick barrier walls and door slab

• 1-Hour Fire Protection

Rated at 1500°





FINANCIAL

AMUSEMENT

HOSPITALITY

GAMING

RESTAURANTS

JEWELRY

CANNABIS

















INTERNATIONAL EUROVAULT EVRH





Fascia Panel

High tensil strength hardplate made of drill resistant, polished stainless steel

U.L. Listed Lock

All safes come standard with U.L. Listed Group IIM combination lock with satin finish dial, dial ring & handle. Electronic digital lock optional





Activated Depository Slot

Accumulated cash can be transferred through a tamperproof slot into a secured inner compartment as a deterrent to armed robbery and internal theft. The EVRH offers excellent burglary and fire resistant protection by providing a temporary storage for excess cash throughout the day.

Specifications

Model	Interior H x W x D (in)	Exterior H x W x D (in)	Weight (lbs)	Capacity (cu ft)	Shelves
EVRH	24 x 17 x 17	28 x 21 x 23½	625	4.2	0

Add 2" to exterior depth for hinge & handle projection.

Door Swing Dimensions

Model	Dimensions (in)			
Model	A	В	C	
EVRH	17	421/2	381/4	




Optional Electronic Locks

Electronic digital pushbutton locks with operational features such as programmable combinations, multiple user interface, time delay, and auditing are available

and can be configured with electronic lock devices from LaGard, Kaba Mas, Sargent & Greenleaf, or Millennium Globaloks.

Door Swing Projections



Security Installation Platform



Each International Eurovault EVRH Safe comes equipped with our exclusive Security Installation Platform (SIP), an innovation that ensures accurate and secure installation.

Distributed by:



FIRE RESISTANT SAFE: 1-HOUR RATING
Safe was tested by an independent
laboratory in a furnace at temperatures up
to 1500°F for a period of 1 hour. Interior
temperatures did not exceed 350°F.

SAFESandMORE.com

Text or Call: 888-717-4819 support@safesandmore.com