INTERNATIONAL FORTRESS TL-30X6

Six-sided composite protection plus 2-hour fire protection

Six-sided Composite Protection

Revolutionary ceramic matrix material with steel layers on six sides resists all forms of attack

Boltwork

Massive 1.5" chrome plated bolts automatically extend with closed door

Door and Body

Inner and outer layers of electrically welded steel combine with composite material for superior burglary protection

• Locks

Includes dual Underwriters Laboratories Group 2M combination locks that relock during an attack; optional high security keylocks or electronic combination locks can be added

2-Hour Fire Protection

Independent laboratory tested at temperatures up to 1850°F for a period of 2 hours. Interior temperatures did not exceed 350°F.





FINANCIAL

AMUSEMENT

HOSPITALITY

GAMING

RESTAURANTS

JEWELRY

CANNABIS





















INTERNATIONAL FORTRESS TL-30X6

Specifications

















36	FX-7236

Model	Interior H x W x D (in)	Exterior H x W x D (in)	Weight (lbs)	Capacity (cu ft)	Shelves
FX-2524	25 x 24 x 20	29 x 29 x 29	1,800	6.9	1
FX-3524	35 x 24 x 20	40 x 29 x 28	1,996	9.7	2
FX-4524	45 x 24 x 20	50 x 29 x 28	2,375	12.5	3
FX-5524	55 x 24 x 20	60 x 29 x 28	2,751	15.3	4
FX-6528	65 x 28 x 20	70 x 33 x 28	3,402	21.1	5
FX-6034*	60 x 34 x 20	65 x 39 x 28	3,554	23.6	5
FX-6536	65 x 36 x 22	70 x 41 x 30	4,097	29.7	5
FX-7236	72 x 36 x 26	77 x 41 x 36	4,750	39	5


^{*}Special order 8 – 12 weeks. Left hand door swings also available by special order

Door Swing Dimensions

Model	Dimensions (in)			
	A	В	C	
FX-2524	24	57½	56	
FX-3524	24	57 ½	56	
FX-4524	24	57 ½	56	
FX-5524	24	57 ½	56	
FX-6528	28	641/2	66	
FX-6034*	34	66½	72	
FX-6536	36	741/2	77	
FX-7236	36	74½	77	

^{*}Add 2" to depth for hinge & handle projection Add 4" to height for removable metal transport base

Door Swing Projections







Distributed by:



SAFESandMORE.com

Text or Call: 888-717-8149 support@safesandmore.com